# **ANGLE IRON UTILITY**









A-Frame Tongue

**DOT-Approved Lighting** 

Fold-Flat HD Ramp Gate

Ramp Gate with Handle





### SURE-TRAC DIFFERENCE

Fold-Flat HD Ramp Gate with Handle (New) Self-Retained Gate Pins Zinc-Plated Jack

#### **FEATURES**

DOT-Approved Lights Gel-Filled Electrical Connectors Pressure-Treated 2 x 6 Decking

Easy-Lube Hubs 15" Radial Tires

Board Retainers Front and Back HD Tread Plate Fenders

### OPTIONS

Gate Options Spare Tire Mount Wheel Upgrades Spare Tire Color Options Contact Your Local Dealer for More Options







Wholesale Dealer | SMART - CONFIDENT - PROVEN

## **2018 SPECIFICATIONS FOR ANGLE IRON UTILITY**

	5 x 8	5 x 10	6 x 10	6 x 12	7 x 12	7 x 16
GVWR (lbs)	2990	2990	2990	2990	2990	7000
GAWR (lbs/axle)	3500	3500	3500	3500	3500	3500
Curb Weight	890	960	990	1115	1300	1820
Payload	2100	2030	2000	1875	1690	5180
Frame	3 x 2 x 3/16				3 x 2 x 1/4	
Cross Members	3 x 2 x 3/16 (24" On-Center)					
Top Rail	2 x 2 x 1/8 Angle					
Tongue	A-Frame 3" Channel				A-Frame 4" Channel	
Uprights	2 x 2 x 1/8 Angle					
Coupler	2" Ball				2-5/16" Ball	
Jack	Zinc Plated, 2K Top Wind, Coupler Mounted					
Fenders	Tread Plate, Square Rolled with Backer				Tread Plate, Double Brake with Backer	
Easy Lube Axles	Cambered Idler with Brake Flange				Cambered Brake and Idler	
Suspension	Leaf Spring				Equalized Leaf Spring	
Tires	205/75R15 LRC					
Wheels	15", 5 on 4.5, Radial Tires					
	White Spoke					
Decking	2 x 6 Pressure Treated Pine					
Lights	DOT Approved Lights					
Electric Plug	4 Way Flat				7 Pole RV Molded Flat Blade	
Finish	Powder Coated High Gloss Black					
Overall Length	137"	161"	161"	185"	185"	233"
Bed Length	96"	120"	120"	144"	144"	192"
Bed Width	61.5"	61.5"	71.5"	71.5"	71.5"	81.5"
Deck Height	18"	18"	18"	18"	18"	18"
Coupler Height	16"	16"	16"	16"	16"	16"
Gate	2 x 2 Tube, Mesh Covered, Full Width Ramp Gate with Handle					



