

ST CONTRACTOR PRO



Shown with optional Tool Crib, Ladder Racks, Front Ladder, Platform, and Barn Doors

Standard Features

Height

- 6'6" Interior Height

Frame

- 6x2 Tube Frame and Tongue
- 6" Extended Tongue
- Tri-Tongue on 8.5' Wides
- 16" On-Center Tube Wall Studs
- 12" On-Center C-Channel Floor Crossmembers
- 16" On-Center Tube Roof Bows
- Flat Deck
- X-Braced Walls, ALL wall posts have 4"x4" gussets reinforced to frame and 9"x14" Corner Gussets

Hitch

- 7-Way Molded Plug
- 2-5/16 Inch Adjustable Height Coupler
- Safety Chains
- 7K Set-Back Jack

Axle

- Torsion Axles

Wheels/Tires

- E-Z Lube Hubs
- Radial Tires on Aluminum Wheels (up to 14K)
- Radial Tires on Black Wheels (16K)

Interior

- 3/8 Inch Plywood Wall Liner w/Aluminum H-Trim (Eliminates Stapled Luan Trim)
- 3/4 Inch Engineered Wood Flooring
- Thermo-Sheath® Ceiling Liner (Above Roof Bows)
- Flat Front Full Width Interior Wall

12 Volt Electrical

- (2) 12 Volt Wall Mounted LED Dome Light (380 Lumens) w/ (2) 3-Way Wall Switches
- LED 6" Oval Tail Lights w/Rubber Mounted 3/4" Bullet Marker Lights (All Clear Lens)
- **Integrated Backup Lights**
- (3) Amber Front Marker Lights in Fiberglass Cap

Exterior

- .030 Smooth Aluminum Exterior
- Screw-less Exterior
- 24" Stoneguard W/Top Trim
- Seamless Aluminum Roof w/3" Top Trim
- 3" Bottom Trim
- Aluminum Fenders
- Rubberized Undercoating
- Polyethylene Vapor Barrier
- Flow-Through Scoop Vents

Door

- 32"x70" RV Side Door w/Barlock Add-On
- Heavy Duty Ramp Door with Integrated Transition or Double Rear Barn Doors w/Cam Bar
- Ramp Ratings - 8.5' wide = 4,100 lb.
- Aluminum Door Holders on Side Door and Rear Double Doors

Limited 3-Year Warranty

SPECIFICATIONS

		10K	14K	16K
Model #	16'	STBNRP10220TA-140	STBNRPD10220TA-100	STBNRPD10220TA-140
	18'	STBNRP10224TA-140	STBNRPD10224TA-100	STBNRPD10224TA-140
	20'	STBNRP10228TA-140	STBNRPD10228TA-100	STBNRPD10228TA-140
	24'	STBNRP10232TA-140	STBNRPD10232TA-100	STBNRPD10232TA-140
GVWR (lbs)		9900	14000	16000
GAWR (lbs/axle)		5200	7000	8000
Curb Weight	16'	3450	3600	4100
	18'	3600	3750	4250
	20'	3750	4080	4580
	24'	4050	4780	5280
Payload	16'	6450	10400	11900
	18'	6300	10250	11750
	20'	6150	9920	11420
	24'	5850	9220	10720
Frame		6 x 2, 3/16" Tube	6 x 2, 1/8" Tube	8 x 2 Tube
Cross Members		Tube (12" On-Center)	Tube (12" On-Center)	
Tongue		6 x 2, 3/16" Tube		8 x 2 Tube
Wall Studs		Tube (16" On-Center)		
Roof Bows		Tube (16" On-Center)		
Coupler		2 5/16" Ball	Adjustable 2 5/16" Ball	Adj. 4-Bolt Pintle
Jack		7K Dropleg		HD 12K Jack
Fenders		Aluminum Teardrop		
Easy Lube Axles		22.5 Degree Up Torsion		
Tires		225/75R15 LRD	235/80R16 LRE	215/75R17 LRH
Wheels		15", 6 on 5.5, Radial	16", 8 on 6.5, Radial	17.5", 8 on 6.5, Radial
Wheels		Aluminum		
Flooring		Engineered Wood		
Lights		All LED Lights w/ Integrated Backup Lights		
Electric Plug		7 Pole RV Molded Flat Blade		
Exterior		.030 Aluminum		
Overall Length	16'	303"		
	18'	351"		
	20'	399"		
	24'	447"		
Overall Width		102"		
Overall Height		104"	106"	106"
Interior Height		84"		
Interior Width		97" (80.5" Between Fender Box)		
Interior Length	16'	249"		
	18'	297"		
	20'	345"		
	24'	393"		
Floor Height		21"	23"	23"
Rear Door Opening (WxH)		92" x 82.50"		
Ramp Door Capacity (lbs.)		4100		



Shown with optional Tool Crib, Ladder Racks, Front Ladder, Platform, and Barn Doors