

ST CONTRACTOR PRO



Shown with optional Tool Crib, Ladder Racks, Front Ladder, Platform, and Barn Doors

Standard Features

Height

- 6'6" Interior Height

Frame

- 6x2 Tube Frame and Tongue
- 6" Extended Tongue
- Tri-Tongue on 8.5' Wides
- 16" On-Center Tube Wall Studs
- 12" On-Center C-Channel Floor Crossmembers
- 16" On-Center Tube Roof Bows
- Flat Deck
- X-Braced Walls, ALL wall posts have 4"x4" gussets reinforced to frame and 9"x14" Corner Gussets

Hitch

- 7-Way Molded Plug
- 2-5/16 Inch Adjustable Height Coupler
- Safety Chains
- 7K Set-Back Jack

Axle

- Torsion Axles

Wheels/Tires

- E-Z Lube Hubs
- Radial Tires on Aluminum Wheels (up to 14K)
- Radial Tires on Solid Silver Wheel (16K)

Interior

- 3/8 Inch Plywood Wall Liner w/Aluminum H-Trim (Eliminates Stapled Luan Trim)
- 3/4 Inch Engineered Wood Flooring
- Thermo-Sheath® Ceiling Liner (Above Roof Bows)
- Flat Front Full Width Interior Wall

12 Volt Electrical

- (2) 12 Volt Wall Mounted LED Dome Light (380 Lumens) w/ (2) 3-Way Wall Switches
- LED 6" Oval Tail Lights w/Rubber Mounted 3/4" Bullet Marker Lights (All Clear Lens)
- ***Integrated Backup Lights**
- (3) Amber Front Marker Lights in Fiberglass Cap

Exterior

- .030 Smooth Aluminum Exterior
- Screw-less Exterior
- 24" Stoneguard W/Top Trim
- Seamless Aluminum Roof w/3" Top Trim
- 3" Bottom Trim
- Aluminum Fenders
- Rubberized Undercoating
- Polyethylene Vapor Barrier
- Flow-Through Scoop Vents

Door

- 32"x70" RV Side Door w/Barlock Add-On
- Heavy Duty Ramp Door with Integrated Transition or Double Rear Barn Doors w/Cam Bar
- Ramp Ratings - 8.5' wide = 4,100 lb.
- Aluminum Door Holders on Side Door and Rear Double Doors

Limited 3-Year Warranty

* Denotes New for 2020

SPECIFICATIONS

		10K	14K	16K
Model #	16'	STBNRP10220TA-140	STBNRPD10220TA-100	STBNRPD10220TA-140
	18'	STBNRP10224TA-140	STBNRPD10224TA-100	STBNRPD10224TA-140
	20'	STBNRP10228TA-140	STBNRPD10228TA-100	STBNRPD10228TA-140
	24'	STBNRP10232TA-140	STBNRPD10232TA-100	STBNRPD10232TA-140
GVWR (lbs)		14000	9900	14000
GAWR (lbs/axle)		7000	5200	7000
Curb Weight	16'	5440	4900	5440
	18'	5640	5100	5640
	20'	5960	5440	5960
	24'	6880	6360	6880
Payload	16'	8560	5000	8560
	18'	8360	4800	8360
	20'	8040	4460	8040
	24'	7120	3540	7120
Frame		6 x 2, 3/16" Tube	6 x 2, 1/8" Tube	6 x 2, 3/16" Tube
Cross Members		Tube (16" On-Center)	C-Channel (16" On-Center)	Tube (16" On-Center)
Tongue		6 x 2, 3/16" Tube	6 x 2, 1/8" Tube	6 x 2, 3/16" Tube
Wall Studs		Tube (16" On-Center)		
Roof Bows		Tube (16" On-Center)		
Coupler		Adjustable 2 5/16" Ball		
Jack		7K Dropleg		
Fenders		Aluminum Teardrop		
Easy Lube Axles		Torsion (Includes 12" Spread)		
Tires		235/80R16 LRE	225/75R15 LRD	235/80R16 LRE
Wheels		16", 8 on 6.5, Radial	15", 6 on 5.5, Radial	16", 8 on 6.5, Radial
Wheels		Aluminum		
Flooring		Engineered Wood	Rubber Tread Plate	
Lights		All LED Lights w/ Integrated Backup Lights		
Electric Plug		7 Pole RV Molded Flat Blade		
Exterior		.030 Aluminum		
Overall Length	16'	303"		
	18'	351"		
	20'	399"		
	24'	447"		
Overall Width		102"		
Overall Height		112"	110"	112"
Interior Height		84"		
Interior Width		97" (80.5" Between Fender Box)		
Interior Length	16'	249"		
	18'	297"		
	20'	345"		
	24'	393"		
Floor Height		23"	21"	23"
Rear Door Opening (WxH)		92" x 82.50"		
Ramp Door Capacity (lbs.)		4100		



Shown with optional Tool Crib, Ladder Racks, Front Ladder, Platform, and Barn Doors