

ST CONTRACTOR PRO BULLNOSE

HEIGHT

- 6'6" Interior Height

FRAME

- 6" x 2" Tube Frame and Tongue
- 6" Extended Tongue
- Tri-Tongue on 8.5' Wides
- 16" On-Center Tube Wall Studs
- 12" On-Center C-Channel Floor
- Crossmembers
- 16" On-Center Tube Roof Bows
- Flat Deck
- X-Braced Walls, ALL wall posts have 4"x4" gussets reinforced to frame and 9"x14" Corner Gussets

HITCH

- 7-Way RV-Style Molded Plug
- Adjustable 2-5/16" Coupler (10K & 14K Models)
- Adjustable 4-Bolt Pintle Eye Coupler (16K Models)
- Setback 7K Drop Leg Jack (10K & 14K Models)
- Setback HD 12K Drop Leg Jack (16K Models)
- Safety Chains

AXLES

- Torsion Axles
- Easy Lube Hubs

WHEELS / TIRES

- Radial Tires on Aluminum Wheels
- Radial Tires on Solid Silver Wheel (16K Models)

INTERIOR

- 3/8" Engineered Wood Wall Liner with Aluminum H-Trim (Eliminates Stapled Lauan Trim)
- 3/4" Engineered Wood Flooring
- Thermo-Sheath® Ceiling Liner (Above Roof Bows)
- Flat Front Full-Width Interior Wall

12-VOLT ELECTRICAL

- (2) 12-Volt Wall Mounted LED Dome Light (380 Lumens) with (2) 3-Way Wall Switches
- (3) Amber Front Marker Lights in Fiberglass Cap
- All LED Exterior Lights
- Integrated Backup Lights

EXTERIOR

- .030 Smooth Aluminum Exterior
- Screwless Exterior
- 24" Stoneguard with Top Trim
- Seamless Aluminum Roof with 3" Top Trim
- 3" Bottom Trim
- Aluminum Fenders
- Rubberized Undercoating
- Polyethylene Vapor Barrier
- Flow-Through Scoop Vents

DOORS

- 32" x 70" RV Side Door with Barlock Add-On and Aluminum Door Holder
- Heavy Duty Ramp Door with Integrated Transition
 - **OR** Rear Double Doors with Aluminum Rear Door Holders
- Ramp Rating – 8.5' Wide = 4100 lb.





CONTRACTOR PRO BULLNOSE

		10K	14K
Model #	16'	STBNCP10216TA-100	STBNCP10216TA-140
	18'	STBNCP10218TA-100	STBNCP10218TA-140
	20'	STBNCP10220TA-100	STBNCP10220TA-140
	24'	STBNCP10224TA-100	STBNCP10224TA-140
	28'	N/A	STBNCP10228TA-140
GVWR (lbs)		9900	14000
GAWR (lbs/axle)		5200	7000
Curb Weight	16'	3450	3600
	18'	3600	3750
	20'	3750	4080
	24'	4050	4780
	28'	N/A	5060
Payload	16'	6450	10400
	18'	6300	10250
	20'	6150	9920
	24'	5850	9220
	28'	N/A	8940
Frame		6x2, 1/8" Tube	6 x 2, 3/16" Tube
Cross Members		C-Channel (12" On-Center)	Tube (12" On-Center)
Tongue		6x2, 1/8" Tube	6 x 2, 3/16" Tube
Wall Studs		Tube (16" On-Center)	
Roof Bows		Tube (16" On-Center)	
Coupler		Adjustable 2-5/16" Ball Coupler	
Jack		Setback 7K Drop Leg Jack	
Fenders		Aluminum Teardrop	
Axles		Torsion, Easy Lube Hubs with Brakes	
Tires		225/75R15 LRD	235/80R16 LRE
Wheels		15", 6 on 5.5, Radial	16", 8 on 6.5, Radial
Flooring		Aluminum Teardrop	
Lights		All LED Lights w/ Integrated Backup Lights	
Electric Plug		7-Way RV-Style Molded Plug	
Exterior		Screwless .030 Aluminum	
Overall Length	16'	252"	
	18'	279"	
	20'	303"	
	24'	351"	
	28'	399"	
Overall Width		102"	
Overall Height		104"	106"
Interior Height		78"	
Interior Width / Between Fenders		97" / 80.5"	
Interior Length	16'	192"	
	18'	216"	
	20'	240"	
	24'	288"	
	28'	336"	
Floor Height		21"	23"
Ramp Door Capacity (lbs.)		4100	
Rear Door Opening (W x H)		90" x 72.50"	90" x 72.50"