

| | 16', 14K | 16' + 4', 14K | 18', 14K | 18' + 4', 14K |
|----------------------|---|------------------|-----------------|------------------|
| Model # | ST8216TBE-B-140 | ST82164TBE-B-140 | ST8218TBE-B-140 | ST82184TBE-B-140 |
| GVWR | 14000 | | | |
| GAWR | 7000 | | | |
| Curb Weight | 3120 | 3520 | 3320 | 3730 |
| Payload | 10880 | 10480 | 10680 | 10270 |
| Frame | 6" C-Channel and Tube | | | |
| Tilting Deck Frame | 6" Tube | | | |
| Cross Members | 3" C-Channel (16" On-Center) | | | |
| Tongue | 6" C-Channel | | | |
| Coupler | Adjustable 2-5/16" Ball Coupler | | | |
| Jack | Setback HD 12K Drop Leg Jack | | | |
| Fenders | HD Tread Plate | | | |
| Axles | 4" Drop Axles, Easy Lube Hubs with Brakes | | | |
| Suspension | Slipper Spring | | | |
| Tires | 235/80R16 LRE | | | |
| Wheels | 16", 8 on 6.5, Radial | | | |
| Decking | 2 x 6 Treated Pine | | | |
| Lights | All LED Lights | | | |
| Electric Plug | 7-Way RV-Style Molded Plug | | | |
| Finish | Powder Coated High Gloss Black | | | |
| Length (Overall/Bed) | 261" / 198" | 309" / 246" | 285" / 222" | 333" / 270" |
| Between Fenders | 82" | | | |
| Deck Height | 20" | | | |
| Coupler Height | Adjustable 19" - 27" | | | |
| Tilt Angle | 11.5 Degree Tilt Angle | | | |

Additional configurations available. Refer to the dealer portal or contact your sales representative for more information.

ADDITIONAL FEATURES

Nested Frame Tapered Entry for Full Width Loading **HD Tube Bulkhead** Safety Chains Breakaway Switch with Battery EverLink™ Wiring Harness Sealed Brake Connections HD Diamond Plate Knife Edge Tail (4) D-Rings Stake Pockets and Rub Rail Spare Tire Carrier Hydraulic Dampener Limited 3-Year Warranty



