

GALVANIZED HIGH SIDE UTILITY









Self-Retained Gate Pins

2000 lb Tie-Downs

Board Retainers

Sealed Rubber Mounted LED Lights





Designed with High Tensile Steel to provide the ultimate strength-to-weight ratio

SURE-TRAC DIFFERENCE

Fold-Flat HD Ramp Gate Spring-Assist Ramp Gate Self-Retained Gate Pins Zinc-Plated Setback Jack Sealed LED Lights Protected Wiring

FEATURES

Gel-Filled Electrical Connectors Pressure-Treated 2 x 6 Decking

Easy-Lube Hubs 15" Radial Tires

100% Galvanized Frame and Side Panels Zinc-Plated Coupler Board Retainers Front and Back Tie Downs Inside Bed (4 SA, 6 TA) Spare Tire Carrier

OPTIONS

Spare Tire Wheel Options Contact Your Local Dealer for More Options

Patent No. 8,985,664, 9,254,777 & 9,403,567







Wholesale Dealer | SMART - CONFIDENT - PROVEN

2018 SPECIFICATIONS FOR GALVANIZED HIGH SIDE UTILITY

	5 x 8	5 x 10	6 x 10	6 x 12	7 x 12	7 x 16
GVWR (lbs)	2990	2990	2990	2990	2990	7000
GAWR (lbs/axle)	3500	3500	3500	3500	3500	3500
Curb Weight	730	840	940	1060	1090	1630
Payload	2260	2150	2050	1930	1900	5370
Frame	Hi Tensile Galvanized Steel					
Cross Members	Hi Tensile Galvanized Steel					
Tongue	Hi Tensile Galvanized Steel, A-Frame					
Coupler	2" Ball 2 5/16" Ball					
Jack	Zinc Plated Set-Back Jack					
Fenders	Square Formed Stand On Fenders					
Easy Lube Axles	Cambered Idler					Cambered Brakes
Suspension	Eye to Eye Spring					
Tires	205/75R15					
Wheel Size	15", 5 on 4.5, Radial Tire					
Wheels	Silver Mod					
Decking	2 x 6 Pressure Treated Decking					
Lights	All LED Lights					
Electric Plug	4 Way Flat					7 Pole RV Molded Flat Blade
Finish	Galvanized					
Overall Length	141"	165"	165"	189"	189"	240"
Bed Length	98"	122"	122"	146"	146"	194"
Bed Width	59.75"	59.75"	71.75"	71.75"	81.75"	81.75"
Deck Height	18"	18"	18"	18"	18"	18"
Side Rail Height	12"	12"	12"	12"	12"	12"
Coupler Height	16"	16"	16"	16"	16"	16"
Gate	Galvanized Spring Assist / Fold Flat Gate					





