



HD LOW PROFILE POWER TILT DECKOVER



110 Volt
Battery Charger



Shown with Color Option Red



Shown with Optional Heavy Duty
I-Beam Gooseneck



SURE-TRAC DIFFERENCE

Slipper Spring Suspension
All LED Lights
Everlink™ - High-Performance Wiring Harness
Sealed Brake Connections
Undercoated Main Frame

FEATURES

Pressure-Treated 2 x 6 Decking
Deep Cycle Marine Grade Battery
110 Volt Battery Charger

Oil Filled Hubs (Tandem Dual)
16" Radial Tires
Slipper Springs

HD 12K Dropleg Jack
Spare Tire Carrier
HD Stake Pockets and Rub Rail
(6) HD D-Rings
Chain Spools
Side Steps
HD Bulkhead (New)

OPTIONS

Gooseneck
Battery Charger
Decking
Spare Tire
Contact Your Local Dealer for More Options



SMART - CONFIDENT - PROVEN

SURE-TRAC.COM

© 2018 Novae Corporation. All Rights Reserved.





Wholesale Dealer | **SMART - CONFIDENT - PROVEN**

2018 SPECIFICATIONS FOR HEAVY DUTY LOW PROFILE POWER TILT DECKOVER

		8.5 x 22	8.5 x 22 + 4	8.5 x 22	8.5 x 22 + 4	8.5 x 24	8.5 x 24 + 4	8.5 x 24	8.5 x 24 + 4
GVWR (lbs)		15000		17600		22500		25900	
GAWR (lbs/axle)		7000		8000		10000		12000	
Curb Weight	Bumper Pull	4485	5170	4825	5370	6080	6480	6220	6620
	Gooseneck	4775	5460	5115	5660	6340	6740	6480	6880
Payload	Bumper Pull	10515	9830	12775	12230	16420	16020	19680	19280
	Gooseneck	10225	9540	12485	11940	16160	15760	19420	19020
Main Frame		W10 x 12#/ft., I-Beam				W12 x 19#/ft., I-Beam			
Side Rails		6 x 2, 3/16 Wall Tube				6" C-Channel			
Cross Members		3" C-Channel (16" On-Center)				4" C-Channel (16" On-Center)			
Coupler	Bumper Pull	Adjustable Pintle		Adjustable 4 Bolt Pintle					
	Gooseneck	Adjustable 2-5/16 Ball							
Jack	Bumper Pull	Center Mounted 12K Dropleg							
	Gooseneck	Dual HD 12K Jacks with Toolbox							
Axles		E-Z Lube Electric Brake				Oil Bath Bearing			
Suspension		Slipper Leaf Spring							
Tires		235/80R16 LRE		215/75R 17.5 LRH		235/80R16 LRE			
Wheels		16"		17.5"		16"			
		White Spoke		Grey					
Decking		2" Pressure Treated Pine							
Lights		All LED Lights							
Electric Plug		7 Pole RV Molded Flat Blade							
Finish		Primed and Enamel Painted Exterior, Undercoated Main Frame							
Overall Length	Bumper Pull	330"	378"	330"	378"	354"	402"	354"	402"
	Gooseneck	378"	426"	378"	426"	402"	450"	402"	450"
Deck Height		34"	34"	34"	34"	34"	34"	34"	34"
Coupler Height	Bumper Pull	Adjustable 19"-27"							
	Gooseneck	Adjustable 31" - 39-3/4"							
Hydraulic Hoist		Dual Ram (Power Up / Power Down)				Scissor Hoist (Power Up / Power Down)			
Pump		3000 PSI Pump with Reservoir							
Battery		24 Group Deep Cycle Battery							
Load Angle		15 Degrees							



SMART - CONFIDENT - PROVEN

SURE-TRAC.COM

© 2018 Novae Corporation. All Rights Reserved.

