

# ST HD LOW PROFILE HYDRAULIC BEAVERTAIL DECKOVER - GOOSENECK

|                                    | 8.5 X 20+10, 22.5K  | 8.5 X 20+10, 25.9K     | 8.5 X 20+10, 30K           |
|------------------------------------|---|------------------------|----------------------------|
| <b>Model #</b>                     | ST1022010LPD02A-GN-225  | ST1022010LPD02A-GN-259 | ST1022010LPD02A-GN-300     |
| <b>GVWR (lbs)</b>                  | 22500   | 25900                  | 30000                      |
| <b>GAWR (lbs/axle)</b>             | 10000   | 12000                  | 16000                      |
| <b>Curb Weight</b>                 | 6520  | 6680                   | 7580                       |
| <b>Payload</b>                     | 15980   | 19220                  | 22420                      |
| <b>Main Frame</b>                  | W12 x 19#/ft., I-Beam   |                        | W12 x 19#/ft. I-Beam       |
| <b>Side Rails</b>                  | 6" C-Channel  |                        |                            |
| <b>Cross Members</b>               | 3" C-Channel (16" On-Center)  |                        | 3" Channel (12" On-Center) |
| <b>Beaver Tail</b>                 | Wood Deck   |                        |                            |
| <b>Gooseneck Coupler</b>           | Adjustable 2-5/16" Ball Coupler   |                        |                            |
| <b>Jack</b>                        | Dual Setback HD 12K Drop Leg Jacks with Toolbox (Between Uprights), Tool Tray and Winch Receiver Tube (In Neck) |                        |                            |
| <b>Axles</b>                       | Oil Bath Hubs with Brakes   |                        |                            |
| <b>Suspension</b>                  | Slipper Leaf Spring   |                        |                            |
| <b>Tires</b>                       | 235/80R16 LRE   |                        | 215/75R17.5 LRH            |
| <b>Wheels</b>                      | 16", 8 on 6.5, Radial   |                        | 17.5", 8 on 6.5, Radial    |
| <b>Decking</b>                     | 2 x 6 Pressure Treated Pine   |                        |                            |
| <b>Lights</b>                      | All LED Lights  |                        |                            |
| <b>Electric Plug</b>               | 7-Way RV-Style Molded Plug  |                        |                            |
| <b>Finish</b>                      | Powder Coat High Gloss Black  |                        |                            |
| <b>Overall Length</b>              | 497"  |                        |                            |
| <b>Deck Height</b>                 | 32"   |                        |                            |
| <b>Coupler Height</b>              | Adjustable 31" - 39.75"   |                        |                            |
| <b>Beavertail Payload</b>          | 5000 lbs  |                        |                            |
| <b>Beavertail Lifting Capacity</b> | 8000 lbs (Center of Tail)   |                        |                            |
| <b>Load Angle</b>                  | 15 Degrees  |                        |                            |
| <b>Battery</b>                     | Group 24 Deep Cycle   |                        |                            |

## HD LOW PROFILE HYDRAULIC BEAVERTAIL DECKOVER - GOOSENECK FEATURES

|  |   |  |
|--|---|--|
| <ul style="list-style-type: none"> <li>Pierced I-Beam Frame</li> <li>Cross-Trac™ Bracing</li> <li>I-Beam Gooseneck</li> <li>Adjustable 2-5/16" Gooseneck Coupler</li> <li>Safety Chains</li> <li>7-Way RV-Style Molded Plug</li> <li>Breakaway Switch with Battery</li> <li>EverLink™ Wiring Harness</li> <li>Sealed Brake Connections</li> <li>Dual Setback HD 12K Drop Leg Jacks with Toolbox</li> <li>10' Hydraulic Beavertail</li> </ul> | <ul style="list-style-type: none"> <li>HD Slipper Spring Axles</li> <li>48" Axle Spread</li> <li>Oil Filled Hubs</li> <li>16" Radial Tires (22.5K &amp; 25.9K Models)</li> <li>17.5" Radial Tires (30K Models)</li> <li>Silver Wheels</li> <li>Wheel Assembly, 235 80R16 LRE 4.77 Silver Dual (22.5K &amp; 25.9K Models)</li> <li>Wheel Assembly, 215 75R17.5 LRH Silver Dual (30K Models)</li> <li>Powder Coat Finish</li> <li>2" x 6" Pressure Treated Decking</li> <li>Diamond Plate Deck Over Wheels</li> </ul> | <ul style="list-style-type: none"> <li>(8) 5/8" D-rings</li> <li>Chain Spools</li> <li>Stake Pockets and Rub Rail</li> <li>Spare Tire Carrier</li> <li>Side Steps</li> <li>Underbody Side Mount Control Box</li> <li>All LED Lights</li> <li>Deep Cycle Battery</li> <li>Battery Charger, 110-Volt</li> <li>HD 5" Bore Twin Lift Cylinder in Beavertail</li> <li>Power-Up, Power-Down Hydraulics (Dual Ram)</li> </ul> |
|--|---|--|

