

ST LANDSCAPE PRO ROUND TOP

HEIGHT

- 6'6" Interior Height

FRAME

- 6" x 2" Tube Frame and Tongue
- 6" Extended Tongue
- Tri-Tongue on 8.5' Wides
- 16" On-Center Tube Wall Studs
- 12" On-Center C-Channel Floor Crossmembers
- 16" On-Center Tube Roof Bows
- Flat Deck with Optional 24" or 48" Beavertail
- X-Braced Walls, ALL wall posts have 4"x4" gussets reinforced to frame and 9"x14" Corner Gussets

HITCH

- 7-Way RV-Style Molded Plug
- Adjustable 2-5/16" Coupler
- Setback 7K Drop Leg Jack
- Safety Chains

AXLES

- Torsion Axles
- Easy Lube Hubs

WHEELS / TIRES

- Radial Tires on Aluminum Wheels

LANDSCAPE ACCESSORIES

- Steel Fold-Down Workbench
 - **OR** (1) HD 24" Deep Wood Shelf with Rubber Tread Flooring and Front Lip.
- 48" Posts with (3) TB-01 Gridiron Trimmer Brackets

INTERIOR

- 3/8" Engineered Wood Wall Liner w/ Aluminum H-Trim (Eliminates Stapled Lauan Trim)
- 3/4" Pressure Treated Plywood Floor
- 3/4" x 11" Plywood Kick Panel around entire perimeter
- Thermo-Sheath® Ceiling Liner (Above Roof Bows)
- Flat Front Full-Width Interior Wall

12-VOLT ELECTRICAL

- (2) 12-Volt Wall Mounted LED Dome Light (380 Lumens) with (2) 3-Way Wall Switches
- (3) Amber Front Marker Lights in Fiberglass Cap
- All LED Exterior Lights
- Integrated Backup Lights

EXTERIOR

- .030 Smooth Aluminum Exterior
- Screwless Exterior
- 24" Stoneguard with Top Trim
- .080 Aluminum Roof Cove with Seamless Aluminum Roof
- 3" Bottom Trim
- Aluminum Fenders
- Rubberized Undercoating
- Polyethylene Vapor Barrier
- Flow-Through Scoop Vents
- (2) Non-Powered Roof Vents

DOORS

- 32" x 70" RV Side Door with Barlock Add-On and Aluminum Door Holder
- Super Duty Ramp Door with Integrated Transition
- Ramp Rating – 8.5' Wide = 5250 lb.



ST LANDSCAPE PRO ROUND TOP

		7K	10K
Model #	16'	STRLP10216TA	STRLP10216TA-100
	18'	STRLP10218TA	STRLP10218TA-100
	20'	STRLP10220TA	STRLP10220TA-100
	24'	STRLP10224TA	STRLP10224TA-100
GVWR (lbs)		7000	9900
GAWR (lbs/axle)		3500	5200
Curb Weight	16'	3120	3755
	18'	3270	3980
	20'	-	4205
	24'	-	4655
Payload	16'	3880	6145
	18'	3730	5920
	20'	-	5695
	24'	-	5245
Frame		6x2, 1/8" Tube	
Cross Members		C-Channel (12" On-Center)	
Tongue		6x2, 1/8" Tube	
Wall Studs		Tube (16" On-Center)	
Roof Bows		Tube (16" On-Center)	
Coupler		Adjustable 2-5/16" Ball Coupler	
Jack		Setback 7K Drop Leg Jack	
Fenders		Aluminum Teardrop	
Axles		Torsion, Easy Lube Hubs with Brakes	
Tires		205/75R 15 LRC	225/75R15 LRD
Wheels		15", 5 on 4.5, Radial	15", 6 on 5.5, Radial
Flooring		Engineered Wood	
Lights		All LED Lights w/ Integrated Backup Lights	
Electric Plug		7-Way RV-Style Molded Plug	
Exterior		Screwless .030 Aluminum	
Overall Length	16'	255"	
	18'	279"	
	20'	303"	
	24'	351"	
Overall Width		102"	
Overall Height		107"	107"
Interior Height		81"	
Interior Width / Between Fenders		97" / 80.5"	
Interior Length	16'	184"	
	18'	208"	
	20'	232"	
	24'	280"	
Floor Height		21"	21"
Ramp Door Capacity (lbs.)		5250	
Rear Door Opening (W x H)		90" x 72.50"	90" x 72.50"

14K GVWR Includes Adjustable 2-5/16" Coupler and Setback 7K Drop Leg Jack
16K GVWR (Includes Adjustable 4-Bolt Pintle Eye Coupler and Setback HD 12K Drop Leg Jack