



# PRO SERIES ROUND TOP CARGO



## Standard Features

### Height

- 6'6" Interior Height

### Frame

- 6x2 Tube Frame and Tongue
- 16" On-Center Tube Wall Studs
- 16" On-Center C-Channel Floor Crossmembers
- 24" On-Center Tube Roof Bows
- "WideTrac" Full-Width Interior Walls Without Fender Boxes (on 7' wides)

### Hitch

- 7-Way Molded Plug
- 2-5/16" Coupler on 7K and 10K
- Adjustable 2-5/16" Coupler on 14K
- 4-Bolt Faceplate Pintle on 16K
- Safety Chains
- Zinc-Plated Setback Jack on 7K
- 7K Setback Jack on 10K & 14K
- HD 12K Setback Jack on 16K

### Axle

- **\*Torsion Axles**
- All Wheel Brakes on Tandem Axle Models

### Wheels/Tires

- Easy Lube Hubs
- Radial Tires on Aluminum Wheels (up to 14K)
- Radial Tires on Black Wheels (16K)

### Interior

- 3/8 Inch Plywood Wall Liner w/Aluminum H-Trim (Eliminates Stapled Lauan Trim)
- 3/4" Engineered Wood Flooring
- Thermo-Sheath® Ceiling Liner (Above Roof Bows)

### 12 Volt Electrical

- (2) 12 Volt Wall Mounted LED Dome Light (380 Lumens) w/1 Wall Switch
- LED 6" Oval Tail Lights w/Rubber Mounted 3/4" Bullet Marker Lights (All Clear Lens)
- **\*Integrated Backup Lights**

### Exterior

- .030 Smooth Aluminum Exterior
- Screw-less Exterior
- Bright Front Corners
- Bright Rear Hoop
- 24" Stoneguard w/Top Trim
- .080 Aluminum Roof Cove w/Seamless Aluminum Roof
- 3" Bottom Trim
- Aluminum Fenders
- Rubberized Undercoating
- Polyethylene Vapor Barrier
- Flow-Through Scoop Vents

### Door

- 32"x70" RV Side Door w/Aluminum Door Holder
- Heavy-Duty Rear Ramp Door w/Wood Flap or Rear Double Doors w/Aluminum Rear Door Holders
- Ramp Ratings - 7' wide = 2,250 lb.  
8.5' wide = 4,100 lb.

## Limited 3-Year Warranty

\* Denotes New for 2020

# SPECIFICATIONS

		7' Wide (7K)	7' Wide (10K)	8.5' Wide (7K)	8.5' Wide (10K)
Model #	12'	STR8412TA	STR8412TA-100	-	-
	14'	STR8414TA	STR8414TA-100	-	-
	16'	STR8416TA	STR8416TA-100	STR10216TA	STR10216TA-100
	18'	STR8418TA	STR8418TA-100	STR10218TA	STR10218TA-100
	20'	-	-	STR10220TA	STR10220TA-100
	24'	-	-	STR10224TA	STR10224TA-100
GVWR (lbs)		7000	9900	7000	9900
GAWR (lbs/axle)		3500	5200	3500	5200
Curb Weight	12'	1900	2170	-	-
	14'	2040	2290	-	-
	16'	2120	2400	2960	3130
	18'	2220	2470	3105	3355
	20'	-	-	3330	3580
	24'	-	-	3730	3980
Payload	12'	5100	7730	-	-
	14'	4960	7610	-	-
	16'	4880	7500	4040	6770
	18'	4780	7430	3895	6545
	20'	-	-	3670	6320
	24'	-	-	3270	5920
Frame		6x2 Tube		6x2, 1/8" Tube	
Cross Members		C-Channel (16" On-Center)		C-Channel (16" On-Center)	
Tongue		6x2 Tube		6x2, 1/8" Tube	
Wall Studs		Tube (16" On-Center)		Tube (16" On-Center)	
Roof Bows		Tube (24" On-Center)		Tube (24" On-Center)	
Coupler		2 5/16" Ball		2 5/16" Ball	
Jack		2K Setback	7K Setback	2K Setback	7K Dropleg
Fenders		Aluminum Teardrop		Aluminum Teardrop	
Easy Lube Axles		22.5 Degree Up Torsion		22.5 Degree Up Torsion	
Tires		205/75R 15 LRC	225/75R15 LRD	205/75R 15 LRC	225/75R15 LRD
Wheels		15", 5 on 4.5, Radial	15", 6 on 5.5, Radial	15", 5 on 4.5, Radial	15", 6 on 5.5, Radial
Wheels		Aluminum		Aluminum	
Flooring		Engineered Wood		Engineered Wood	
Lights		All LED Lights w/ Integrated Backup Lights		All LED Lights w/ Integrated Backup Lights	
Electric Plug		7 Pole RV Molded Flat Blade		7 Pole RV Molded Flat Blade	
Exterior		.030 Aluminum		.030 Aluminum	
Overall Length	12'	198"		-	
	14'	222"		-	
	16'	246"		249"	
	18'	270"		273"	
	20'	-		297"	
	24'	-		345"	
Overall Width		102"		102"	
Overall Height		104"		104"	
Interior Height		80"		81"	
Interior Width		81"		97" (80.5" Between Fender Box)	
Interior Length	12'	153"		-	
	14'	177"		-	
	16'	201"		201"	
	18'	225"		225"	
	20'	-		249"	
	24'	-		297"	
Floor Height		21"		21"	
Rear Door Opening (WxH)		74" x 72.50"		90" x 72.50"	
Ramp Door Capacity (lbs.)		2250		2250	

