

ST PRO SERIES WEDGE CARGO

HEIGHT

- 6'6" Interior Height

WEDGE DEPTH

- 18.5" Exterior Wedge Depth

FRAME

- 6" x 2" Tube Frame and Tongue
- 16" On-Center Tube Wall Studs
- 16" On-Center C-Channel Floor Crossmembers
- 24" On-Center Tube Roof Bows
- "WideTrac" Full-Width Interior Walls Without Fender Boxes (7' Models)

HITCH

- 7-Way RV-Style Molded Plug
- 2-5/16" A-Frame Coupler (7K & 10K Models)
- Adjustable 2-5/16" Coupler (14K Models)
- Adjustable 4-Bolt Pintle Eye Coupler (16K Models)
- Setback Zinc Plated Jack (7K Models)
- Setback 7K Drop Leg Jack (10K & 14K Models)
- Setback HD 12K Drop Leg Jack (16K Models)
- Safety Chains

AXLES

- Torsion Axles
- All Wheel Brakes
- Easy Lube Hubs

WHEELS / TIRES

- Radial Tires on Aluminum Wheels
- Radial Tires on Solid Silver Wheels (16K Models)

INTERIOR

- 3/8" Plywood Wall Liner with Aluminum H-Trim (Eliminates Stapled Luan Trim)
- 3/4" Engineered Wood Flooring
- Thermo-Sheath® Ceiling Liner (Above Roof Bows)

12-VOLT ELECTRICAL

- (2) 12-Volt Wall Mounted LED Dome Light (380 Lumens) with (1) Wall Switch
- All LED Exterior Lights
- Integrated Backup Lights

EXTERIOR

- .030 Smooth Aluminum Exterior
- Screwless Exterior
- 24" Stoneguard with Top Trim
- Seamless Aluminum Roof with 3" Top Trim
- Bright Nose Cap & Front Corners
- Bright Rear Hoop
- 3" Bottom Trim
- Aluminum Fenders
- Rubberized Undercoating
- Polyethylene Vapor Barrier
- Flow-Through Scoop Vents

DOORS

- 32" x 70" RV Side Door with Aluminum Door Holder
- Heavy-Duty Rear Ramp Door with Wood Flap
 - **OR** Rear Double Doors with Aluminum Rear Door Holders
- Ramp Ratings –
 - 7' wide = 2,250 lb.
 - 8.5' Wide = 4,100 lb.





PRO SERIES WEDGE CARGO

		7' Wide (7K)	7' Wide (10K)	8.5' Wide (7K)	8.5' Wide (10K)
Model #	12'	STW8412TA	STW8412TA-100	-	-
	14'	STW8414TA	STW8414TA-100	-	-
	16'	STW8416TA	STW8416TA-100	STW10216TA	STW10216TA-100
	18'	STW8418TA	STW8418TA-100	STW10218TA	STW10218TA-100
	20'	-	-	STW10220TA	STW10220TA-100
	24'	-	-	STW10224TA	STW10224TA-100
GVWR (lb.)		7000	9900	7000	9900
GAWR (lb. / axle)		3500	5200	3500	5200
Curb Weight	12'	1900	2150	-	-
	14'	2040	2290	-	-
	16'	2120	2400	2880	3350
	18'	2220	2550	3260	3430
	20'	-	-	3610	3760
	24'	-	-	4170	4420
Payload	12'	5100	7750	-	-
	14'	4960	7610	-	-
	16'	4880	7500	4120	6550
	18'	4780	7350	3740	6470
	20'	-	-	3390	6140
	24'	-	-	2830	5480
Frame		6x2 Tube		6x2 Tube	
Cross Members		C-Channel (16" On-Center)		C-Channel (16" On-Center)	
Tongue		6x2 Tube		6x2 Tube	
Wall Studs		Tube (16" On-Center)		Tube (16" On-Center)	
Roof Bows		Tube (24" On-Center)		Tube (24" On-Center)	
Coupler		2-5/16" A-Frame Coupler		2-5/16" A-Frame Coupler	
Jack		Setback 2K Zinc Plated Jack	Setback 7K Drop Leg Jack	Setback 2K Zinc Plated Jack	Setback 7K Drop Leg Jack
Fenders		Aluminum Teardrop		Aluminum Teardrop	
Easy Lube Axles		Torsion Axles		Torsion Axles	
Tires		205/75R 15 LRC	225/75R15 LRD	205/75R 15 LRC	225/75R15 LRD
Wheels		15", 5 on 4.5, Radial	15", 6 on 5.5, Radial	15", 5 on 4.5, Radial	15", 6 on 5.5, Radial
Wheels		Aluminum		Aluminum	
Flooring		Engineered Wood		Engineered Wood	
Lights		All LED Lights w/ Integrated Backup Lights		All LED Lights w/ Integrated Backup Lights	
Electric Plug		7-Way RV-Style Molded Plug		7-Way RV-Style Molded Plug	
Exterior		Screwless .030 Aluminum		Screwless .030 Aluminum	
Overall Length	12'	198"		-	
	14'	222"		-	
	16'	246"		249"	
	18'	270"		273"	
	20'	-		297"	
	24'	-		345"	
Overall Width		102"		102"	
Overall Height		101"		101"	
Interior Height		78"		78"	
Interior Width		81"		97" (80.5" Between Fender Box)	
Interior Length	12'	153"		-	
	14'	177"		-	
	16'	201"		201"	
	18'	225"		225"	
	20'	-		249"	
	24'	-		297"	
Floor Height		18"		21"	
Rear Door Opening (WxH)		74" x 72.50"		90" x 72.50"	
Ramp Door Capacity (lbs.)		2250		2250	