



7' WIDE PRO SERIES ROUND TOP CARGO

HEIGHT

- 6'6" Interior Height

FRAME

- 6" x 2" Tube Frame and Tongue
- 16" On-Center Tube Wall Studs
- 16" On-Center C-Channel Floor Crossmembers
- 24" On-Center Tube Roof Bows
- "WideTrac" Full-Width Interior Walls Without Fender Boxes (7' Wide Models)

HITCH

- 7-Way RV-Style Molded Plug
- 2-5/16" A-Frame Coupler
- Setback Zinc Plated Jack (7K Models)
- Setback 7K Drop Leg Jack (10K Models)
- Safety Chains

AXLES

- Torsion Axles
- All Wheel Brakes
- Easy Lube Hubs

WHEELS / TIRES

- Radial Tires on Aluminum Wheels

INTERIOR

- 3/8" Engineered Wood Wall Liner with Aluminum H-Trim (Eliminates Stapled Lauan Trim)
- 3/4" Engineered Wood Flooring
- Thermo-Sheath® Ceiling Liner (Above Roof Bows)

12-VOLT ELECTRICAL

- (2) 12-Volt Wall Mounted LED Dome Light (380 Lumens) with (1) Wall Switch
- All LED Exterior Lights
- Integrated Backup Lights

EXTERIOR

- .030 Smooth Aluminum Exterior
- Screwless Exterior
- 24" Stoneguard with Top Trim
- .080 Aluminum Roof Cove with Seamless Aluminum Roof
- Bright Front Corners
- Bright Rear Hoop
- 3" Bottom Trim
- Aluminum Fenders
- Rubberized Undercoating
- Polyethylene Vapor Barrier
- Flow-Through Scoop Vents

DOORS

- 32" x 70" RV Side Door with Aluminum Door Holder
- Heavy-Duty Rear Ramp Door with Wood Flap
 - **OR** Rear Double Doors with Aluminum Rear Door Holders
- Ramp Ratings –
 - 7' wide = 2,250 lb.





7' WIDE PRO SERIES ROUND TOP CARGO

		7K	10K
Model #	12'	STR8412TA	STR8412TA-100
	14'	STR8414TA	STR8414TA-100
	16'	STR8416TA	STR8416TA-100
	18'	STR8418TA	STR8418TA-100
GVWR (lbs)		7000	9900
GAWR (lbs/axle)		3500	5200
Curb Weight	12'	1900	2170
	14'	2040	2290
	16'	2120	2400
	18'	2220	2470
Payload	12'	5100	7730
	14'	4960	7610
	16'	4880	7500
	18'	4780	7430
Frame		6x2 Tube	
Cross Members		C-Channel (16" On-Center)	
Tongue		6x2 Tube	
Wall Studs		Tube (16" On-Center)	
Roof Bows		Tube (24" On-Center)	
Coupler		2-5/16" A-Frame Ball Coupler	
Jack		Setback 2K Zinc Plated Jack	Setback 7K Drop Leg Jack
Fenders		Aluminum Teardrop	
Axles		Torsion, Easy Lube Hubs with Brakes	
Tires		205/75R 15 LRC	225/75R15 LRD
Wheels		15", 5 on 4.5, Radial	15", 6 on 5.5, Radial
Flooring		Engineered Wood	
Lights		All LED Lights w/ Integrated Backup Lights	
Electric Plug		7-Way RV-Style Molded Plug	
Exterior		Screwless .030 Aluminum	
Overall Length	12'	198"	
	14'	222"	
	16'	246"	
	18'	270"	
Overall Width		102"	
Overall Height		104"	
Interior Height		80"	
Interior Width		81"	
Interior Length	12'	153"	
	14'	177"	
	16'	201"	
	18'	225"	
Floor Height		21"	
Ramp Door Capacity (lbs.)		2250	
Rear Door Opening (W x H)		74" x 72.50"	74" x 72.50"



8.5' WIDE PRO SERIES ROUND TOP CARGO

HEIGHT

- 6'6" Interior Height

FRAME

- 6" x 2" Tube Frame and Tongue
- 16" On-Center Tube Wall Studs
- 16" On-Center C-Channel Floor Crossmembers
- 24" On-Center Tube Roof Bows

HITCH

- 7-Way RV-Style Molded Plug
- 2-5/16" A-Frame Coupler (7K & 10K Models)
- Adjustable 2-5/16" Coupler (14K Models)
- Adjustable 4-Bolt Pintle Eye Coupler (16K Models)
- Setback Zinc Plated Jack (7K Models)
- Setback 7K Drop Leg Jack (10K & 14K Models)
- Setback HD 12K Drop Leg Jack (16K Models)
- Safety Chains

AXLES

- Torsion Axles
- All Wheel Brakes
- Easy Lube Hubs

WHEELS / TIRES

- Radial Tires on Aluminum Wheels
- Radial Tires on Solid Silver Wheel (16K Models)

INTERIOR

- 3/8" Engineered Wood Wall Liner with Aluminum H-Trim (Eliminates Stapled Luan Trim)
- 3/4" Engineered Wood Flooring
- Thermo-Sheath® Ceiling Liner (Above Roof Bows)

12-VOLT ELECTRICAL

- (2) 12-Volt Wall Mounted LED Dome Light (380 Lumens) with (1) Wall Switch
- All LED Exterior Lights
- Integrated Backup Lights

EXTERIOR

- .030 Smooth Aluminum Exterior
- Screwless Exterior
- 24" Stoneguard with Top Trim
- .080 Aluminum Roof Cove with Seamless Aluminum Roof
- Bright Front Corners
- Bright Rear Hoop
- 3" Bottom Trim
- Aluminum Fenders
- Rubberized Undercoating
- Polyethylene Vapor Barrier
- Flow-Through Scoop Vents

DOORS

- 32" x 70" RV Side Door with Aluminum Door Holder
- Heavy-Duty Rear Ramp Door with Wood Flap
 - **OR** Rear Double Doors with Aluminum Rear Door Holders
- Ramp Ratings –
 - 8.5' Wide = 4,100 lb.



8.5' WIDE PRO SERIES ROUND TOP CARGO

		7K	10K
Model #	16'	STR10216TA	STR10216TA-100
	18'	STR10218TA	STR10218TA-100
	20'	STR10220TA	STR10220TA-100
	24'	STR10224TA	STR10224TA-100
GVWR (lbs)		7000	9900
GAWR (lbs/axle)		3500	5200
Curb Weight	16'	2960	3130
	18'	3105	3355
	20'	3330	3580
	24'	N/A	3980
Payload	16'	4040	6770
	18'	3895	6545
	20'	3670	6320
	24'	N/A	5920
Frame		6x2, 1/8" Tube	
Cross Members		C-Channel (16" On-Center)	
Tongue		6x2, 1/8" Tube	
Wall Studs		Tube (16" On-Center)	
Roof Bows		Tube (24" On-Center)	
Coupler		2-5/16" A-Frame Ball Coupler	
Jack		Setback 2K Zinc Plated Jack	Setback 7K Drop Leg Jack
Fenders		Aluminum Teardrop	
Axles		Torsion, Easy Lube Hubs with Brakes	
Tires		205/75R 15 LRC	225/75R15 LRD
Wheels		15", 5 on 4.5, Radial	15", 6 on 5.5, Radial
Flooring		Engineered Wood	
Lights		All LED Lights w/ Integrated Backup Lights	
Electric Plug		7-Way RV-Style Molded Plug	
Exterior		Screwless .030 Aluminum	
Overall Length	16'	249"	
	18'	273"	
	20'	297"	
	24'	345"	
Overall Width		102"	
Overall Height		104"	
Interior Height		81"	
Interior Width / Between Fenders		97" / 80.50"	
Interior Length	16'	201"	
	18'	225"	
	20'	249"	
	24'	297"	
Floor Height		21"	
Ramp Door Capacity (lbs.)		2250	
Rear Door Opening (W x H)		90" x 72.50"	90" x 72.50"



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing