



SINGLE AXLE TILT BED EQUIPMENT

	5' x 10' (6K)	6.5' x 12' (7.8K)	6.5' x 12' + 4' (7.8K)	6.5' x 12' (10K)	6.5' x 12' + 4' (10K)
Model #	ST6210SATE-B-060	ST7812SATE-B-078	ST78124SATE-B-078	ST7812SATE-B-100	ST78124SATE-B-100
GVWR (lb.)	6000	7800	7800	9900	9900
GAWR (lb. / axle)	5200	7000	7000	8000	8000
Curb Weight	1360	1900	2100	2200	2400
Payload	4640	5900	5700	7700	7500
Frame	5 x 2 Tube				
Cross Members	C-Channel (16" On-Center)				
Tongue	5 x 2 Tube				
Coupler	Adjustable 2-5/16" Coupler				
Jack	Setback 7K Drop Leg Jack				
Fenders	HD Tread Plate				
Axles	Torsion Axle				
Tires	225/75R15 LRD	235/80R16 LRE		215/75R17.5 LRH	
Wheels	15", 6 on 5.5, Radial	16", 8 on 6.5, Radial		17.5", 8 on 6.5, Radial	17.5", 8 on 6.5, Radial
Decking	2 x 6 Treated Pine				
Lights	All LED Lights				
Electric Plug	7-Way RV-Style Molded Plug				
Finish	Powder Coated High Gloss Black				
Length (Overall/Tilt Deck)	189.5" / 128.5"	214.5" / 152.5"	264.5" / 152.5"	214.5" / 152.5"	264.5" / 152.5"
Between Fenders	62"	78"	78"	78"	78"
Deck Height	17"	19"	19"	21"	21"
Coupler Height	8" - 17"	10" - 19"	10" - 19"	10" - 19"	10" - 19"
Tilt Angle	12 Deg.	11 Deg.	11. Deg	11 Deg.	11. Deg

SINGLE AXLE TILT BED EQUIPMENT FEATURES

HD Tube Bulkhead Adjustable 2-5/16" Coupler Safety Chains 7-Way RV-Style Molded Plug Breakaway Switch with Battery EverLink™ Wiring Harness Sealed Brake Connection Setback 7K Drop Leg Jack HD Reinforced Tread Plate Fenders Torsion Axle	8K Axle(s) with 3-3/8" Brake (10K Models) Easy Lube Hubs 15" Radial Tires (6K Models) 16" Radial Tires (7.8K Models) 17.5" Radial Tires (10K Models) Silver Wheels Wheel Assembly, 225 75R15 LRD (6K Models) Wheel Assembly, 235 80R16 LRE (7.8K Models) Wheel Assembly, 215 75R17.5 (10K Models)	Powder Coat Finish Pressure Treated 2" x 6" Decking Rear Board Retainers HD Diamond Plate Knife Edge Tail (4) 1/2" D-rings Stake Pockets Spare Tire Carrier A-Frame Toolbox All LED Lights Hydraulic Dampener
--	---	--

