

ST TILT BED EQUIPMENT



D-Rings



10K Models Include
2-5/16" Coupler and 7K Set-Back Jack

14K Models Include
Adjustable 2-5/16" Coupler and 7K Set-Back Jack

16K Models Include
Adjustable 4-Bolt Pintle Coupler and HD 12K Jack

TILT BED EQUIPMENT FEATURES

15" Radial Tires (225 75R15 LRD) 5K Axle
16" Radial Tire (235 80R16 LRE.) - 7K Axle
17.5" Radial Tire (215 18R LRH) - 8K Axle
2-5/16" Coupler & 7K Set-Back Jack (10K Models)
Adj. 2-5/16" Coupler & 7K Set-Back Jack (14K Models)
Adj. 4-Bolt Pintle Coupler & 12K Jack (16K Models)
4" Drop Axle
HD Slipper Spring Axle (14K & 16K GVWR)
Easy Lube Hubs
Sealed Brake Connections

C-Channel Full Wrap Tongue
Extended Tongue
Nested Frame
Tapered Entry for 82" Loading Clearance
HD Diamond Plate Knife Edge Tail
HD Tube Bulkhead (NEW)
HD Reinforced Diamond Plate Fenders
(4) 1/2" D-Rings (10K & 14K Models)
(4) 5/8" D-Rings (16K Models)
Stake Pockets and Rub Rail

Spare Tire Carrier
Powder Coat Finish
Pressure Treated 2 x 6 Decking
Rear Board Retainers
7-Way RV-Style Electrical Plug
EverLink(TM) - High Performance Wiring Harness
Cushion Cylinder
Sealed LED Lighting
11.5 Degree Tilt Angle

SPECIFICATIONS

		10K	14K	16K
Model #	16'	ST8216TBE-B-100	ST8216TBE-B-140	ST8216TBE-B-160
	16' + 4'	ST82164TBE-B-100	ST82164TBE-B-140	ST82164TBE-B-160
	18'	ST8218TBE-B-100	ST8218TBE-B-140	ST8218TBE-B-160
	18' + 4'	ST82184TBE-B-100	ST82184TBE-B-140	ST82184TBE-B-160
GVWR		9900	14000	16000
GAWR		5200	7000	8000
Curb Weight	16'	2880	3120	3740
	16' + 4'	3220	3520	4220
	18'	3120	3320	4020
	18' + 4'	3430	3730	4430
Payload	16'	7020	10880	12260
	16' + 4'	6680	10480	11780
	18'	6780	10680	11980
	18' + 4'	6470	10270	11570
Frame		6" C-Channel and Tube		8" C-Channel and Tube
Cross Members		3" C-Channel (16" On-Center)		
Tongue		6" C-Channel		8" C-Channel
Coupler		2-5/16 A-Frame	Adjustable 2-5/16	Adjustable 4 Bolt Pintle
Jack		7K Dropleg		HD 12K Dropleg
Fenders		HD Tread Plate		
Axles		Easy Lube Cambered Brake w/4" Drop		
Suspension		Eye to Eye Spring	Slipper Spring	
Tires		225/75R15 LRD	235/80R16 LRE	215/75R17.5 LRH
Wheels		15", 6 on 5.5, Radial	16", 8 on 6.5, Radial	17.5", 8 on 6.5, Radial
Decking		2 x 6 Treated Pine		
Lights		All LED Lights		
Electric Plug		7 Pole RV Molded Flat Blade		
Finish		Powder Coated High Gloss Black		
Length (Overall/Tilting Deck)	16'	261" / 198"		
	16' + 4'	309" / 198"		
	18'	285" / 222"		
	18' + 4'	333" / 222"		
Between Fenders		82"	82"	82"
Deck Height		20"	20"	20"
Coupler Height		18"	Adjustable 19" - 27"	
Tilt Angle		11.5 Degree Tilt Angle		

