

# TUBE TOP 3-BOARD HIGH SIDE

## ENCLOSED WIRING



## D-RINGS



22" Tall Sides



Fold-Flat HD Ramp Gate

### SURE-TRAC DIFFERENCE

Fold-Flat HD Ramp Gate with Handle  
Spring Assist Ramp Gate  
Self-Retained Gate Pins  
Zinc-Plated Set-Back Jack  
Enclosed Wiring  
2 x 2 Tube Top Rail  
Tube Uprights

### FEATURES

Pressure Treated 2 x 6 Decking  
5/4 Treated Lumber Sides and Front  
Easy-Lube Hubs  
15" Radial Tires  
Sealed LED Lights  
Front and Rear Board Retainers  
Spare Tire Carrier  
(4) 1/2" D-Rings  
HD Tread Plate Fenders  
Powder Coat Finish

### OPTIONS

Gate Upgrades  
Wheel Upgrades  
Color Options

[Contact your Dealer for More Options](#)



# SURE-TRAC

By Novae®

**SMART - CONFIDENT - PROVEN**

## TUBE TOP 3-BOARD HIGH SIDE SPECIFICATIONS

	5 x 8	5 x 10	6 x 10	6 x 12	7 x 12	7 x 14	7 x 16
GVWR	2990	2990	2990	2990	2990	7000	7000
GAWR	3500	3500	3500	3500	3500	3500	3500
Curb Weight	990	1170	1230	1300	1430	2040	2210
Payload	2000	1820	1760	1690	1560	4960	4790
Frame	3 x 2 x 3/16 Angle				3 x 2 x 1/4 Angle		
Cross Members	3 x 2 x 3/16 Angle (24" On-Center)						
Top Rail	2 x 2 Square Tube						
Tongue	3" Channel (A-Frame)				4" Channel (A-Frame)		
Uprights	2 x 2 Square Tube						
Coupler	2" Ball				2 5/16" Ball		
Jack	2K Zinc Plated, Set Back						
Fenders	Tread Plate, Square Rolled with Backer				Tread Plate, Double Brake with Backer		
Easy Lube Axles	Cambered Idler with Brake Flange				Cambered Brake (Both Axles)		
Suspension	Leaf Spring				Equalized Leaf Spring		
Tires	205/75R15 LRC						
Wheels	15", 5 on 4.5, Radial Tire						
Decking	2 x 6 Pressure Treated Pine						
Lights	All LED Lights						
Electric Plug	4 Way Flat				7 Pole RV Molded Flat Blade		
Finish	Powder Coated High Gloss Black						
Overall Length	137"	161"		185"	185"	209"	233"
Bed Length	96"	120"	120"	144"	144"	168"	192"
Between Fenders	59.5"	59.5"	69.5"	69.5"	79.5"	79.5"	79.5"
Deck Height	18"	18"	18"	18"	18"	18"	18"
Coupler Height	16"	16"	16"	16"	16"	16"	16"
Gate	2 x 2 Tube, Mesh Covered, Full Width Spring Assist Ramp Gate with Handle						

