

TUBE TOP UTILITY - SINGLE AXLE

	SA 5' x 8'	SA 5' x 10'	SA 6' x 10'	SA 6' x 12'	SA 7' x 12'	SA 7' x 14'				
Model #	ST6208TA-B-030	ST6210TA-B-030	ST7210TA-B-030	ST7212TA-B-030	ST8212TA-B-030	ST8214TA-B-030				
GVWR (lb.)	2990	2990	2990	2990	2990	2990				
GAWR (lb. / axle)	3500	3500	3500	3500	3500	3500				
Curb Weight	890	960	990	1115	1300	1420				
Payload	2100	2030	2000	1875	1690	1570				
Frame	3 x 2 x 3/16 Angle									
Cross Members	3 x 2 x 3/16 Angle (24" On-Center)									
Top Rail	2 x 2 Square Tube									
Tongue	3" Channel (A-Frame)									
Uprights	2 x 2 square Tube									
Coupler	2" A-Frame Coupler									
Jack	Setback 2K Zinc Plated Jack									
Fenders	Tread Plate, Square Rolled									
Easy Lube Axles	Cambered Idler with Brake Flange									
Suspension	Leaf Spring									
Tires	205/75R15 LRC									
Wheels	15", 5 on 4.5, Radial Tires									
Decking	2 x 6 Pressure Treated Pine									
Lights	All LED Lights									
Electric Plug	4-Way Flat Molded Plug									
Finish	Powder Coated High Gloss Black									
Overall Length	137"	161"	161"	185"	185"	209"				
Bed Length	96"	120"	120"	144"	144"	168"				
Bed Width	61.5"	61.5"	71.5"	71.5"	81.5"	81.5"				
Deck Height	18"	18"	18"	18"	18"	18"				
Coupler Height	16"	16"	16"	16"	16"	16"				
Gate	2 x 2 Tube, Mesh Covered, Full-Width Spring Assist Ramp Gate with Handle									

TUBE TOP UTILITY - SINGLE AXLE STANDARD FEATURES

13" Tall Sides
2" x 2" Tube Top Rail
Tube Uprights
2" A-Frame Coupler
4-Way Flat Molded Plug
Wiring Enclosed in Tubular Steel
Setback 2K Zinc Plated Jack
Fold-Flat HD Ramp Gate with Handle

Spring-Assisted Rear Ramp Gate Self-Retained Gate Pins Tread Plate Fenders Idler Axle Easy Lube Hubs 15" Radial Tires Silver Wheels Wheel Assembly, 205 75R15 LRC Powder Coat Finish Pressure Treated 2" x 6" Decking Front and Rear Board Retainers Stake Pockets Spare Tire Carrier All LED Lights





TUBE TOP UTILITY - TANDEM AXLE

	TA 7' x 14'	TA 7' x 16'	TA 7' x 18'	TA 7' x 20'	TA 7' x 16'	TA 7' x 18'	TA 7' x 20'			
Model #	ST8214TAT-B-070	ST8216TAT-B-070	ST8218TAT-B-070	ST8220TAT-B-070	ST8216TAT-B-100	ST8218TAT-B-100	ST8220TAT-B-100			
GVWR (lb.)	7000	7000	7000	7000	9900	9900	9900			
GAWR (lb. / axle)	3500	3500	3500	3500	5200	5200	5200			
Curb Weight	1700	1820	2200	2410	2530	2650	2770			
Payload	5300	5180	4800	4590	7370	7250	7130			
Frame	3 x 2 x 1	/4 Angle	4 x 3 x 1	5 x 3 x 1/4 Angle						
Cross Members	3 x 2 x 3/16 Angle (24" On-Center)									
Top Rail		2 x 2 Squ	are Tube	3 x 2 Tube						
Tongue		4" Channel	(A-Frame)	5" Channel (A-Frame)						
Uprights	2 x 2 square Tube									
Coupler	2-5/16" A-Frame Coupler									
Jack		Setback 2K Zii	nc Plated Jack	Setback 7K Drop Leg Jack						
Fenders	Tread Plate, Double Brake									
Easy Lube Axles		Cambered Brak	(e (Both Axles)	Cambered Brake (Both Axles)						
Suspension	Equalized Leaf Spring									
Tires			R15 LRC	225/75R 15 LRD						
Wheels		15", 5 on 4.5	, Radial Tires	15", 6 on 5.5, Radial Tires						
Decking	2 x 6 Pressure Treated Pine									
Lights	All LED Lights									
Electric Plug	7-Way RV-Style Molded Plug									
Finish	Powder Coated High Gloss Black									
Overall Length	215"	239"	263"	287"	239"	263"	287"			
Bed Length	168"	192"	216"	240"	192"	216"	240"			
Bed Width	81.5"	81.5"	81.5"	81.5"	81.5"	81.5"	81.5"			
Deck Height	18"	18"	18"	18"	19.5"	19.5"	19.5"			
Coupler Height	16"	16"	16"	16"	17"	17"	17"			
Gate	2 x 2 Tube, Mesh	Covered, Full-Width	Spring Assist Ramp	Reinforced (Ladder Style)						

10K MODELS

INCLUDE SETBACK 7K DROP LEG JACK, 3" X 2" TUBE TOP RAIL AND LADDER REINFORCED GATE

TUBE TOP UTILITY - TANDEM AXLE STANDARD FEATURES

13" Tall Sides
2" x 2" Tube Top Rail (7K Models)
3" x 2" Tube Top Rail (10K Models)
Tube Uprights
2-5/16" A-Frame Coupler
7-Way RV-Style Molded Plug
Breakaway Switch with Battery
Wiring Enclosed in Tubular Steel
Setback 2K Zinc Plated Jack (7K Models)
Setback 7K Drop Leg Jack (10K Models)

Fold-Flat HD Ramp Gate with Handle
Fold-Flat HD Reinforced (Ladder Style) Ramp Gate
with Handle (10K Models)
Spring-Assisted Rear Ramp Gate
Self-Retained Gate Pins
Tread Plate Fenders
Brakes on Both Axles
Easy Lube Hubs
15" Radial Tires

Silver Wheels

Wheel Assembly, 205 75R15 LRC (7K Models)
Wheel Assembly, 225 75R15 LRD (10K Models)
Powder Coat Finish
Pressure Treated 2" x 6" Decking
Front and Rear Board Retainers
Stake Pockets
Spare Tire Carrier
All LED Lights

