

ST TUBE TOP UTILITY - SINGLE AXLE



Tube Top Rail and Uprights



TUBE TOP UTILITY - SINGLE AXLE STANDARD FEATURES

15" Radial Tires (205 75R15 LRC) 3.5K Axle
15" Radial Tires (225 75R15 LRD) 5K Axle
Easy Lube Hubs
2 x 2 Heavy Tube Top Rail for Structural Rigidity
Tube Uprights
2K, Zinc Plated Set-Back Jack

Tread Plate Fenders
Spare Tire Mount
Bead Blasted, Iron Phosphate Washed
10K Models Include a 7K Set-Back Jack, 3x2 Tube
Top Rail, and Ladder Reinforced Gate.
Powder Coat Finish

Fold Flat Ramp Gate with Handle
Spring-Assisted Rear Ramp Gate
Self-Retained Gate Pins
Pressure Treated 2 x 6 Decking
Front and Rear Board Retainers
Wiring Enclosed in Tubular Steel
Sealed LED Lighting

SPECIFICATIONS

	5' x 8'	5' x 10'	6' x 10'	6' x 12'	7' x 12'	7' x 14', SA
Model #	ST6208TA-B-030	ST6210TA-B-030	ST7210TA-B-030	ST7212TA-B-030	ST8212TA-B-030	ST8214TA-B-030
GVWR (lb. / axle)	2990	2990	2990	2990	2990	2990
GAWR (lb. / axle)	3500	3500	3500	3500	3500	3500
Curb Weight	890	960	990	1115	1300	1420
Payload	2100	2030	2000	1875	1690	1570
Frame	3 x 2 x 3/16 Angle					
Cross Members	3 x 2 x 3/16 Angle (24" On-Center)					
Top Rail	2 x 2 Square Tube					
Tongue	3" Channel (A-Frame)					
Uprights	2 x 2 square Tube					
Coupler	2" Ball					
Jack	2K Zinc Plated, Set Back					
Fenders	Tread Plate, Square Rolled					
Easy Lube Axles	Cambered Idler with Brake Flange					
Suspension	Leaf Spring					
Tires	205/75R15 LRC					
Wheels	15", 5 on 4.5, Radial Tires					
Decking	2 x 6 Pressure Treated Pine					
Lights	All LED Lights					
Electric Plug	4 Way Flat					
Finish	Powder Coated High Gloss Black					
Overall Length	137"	161"	161"	185"	185"	209"
Bed Length	96"	120"	120"	144"	144"	168"
Bed Width	61.5"	61.5"	71.5"	71.5"	81.5"	81.5"
Deck Height	18"	18"	18"	18"	18"	18"
Coupler Height	16"	16"	16"	16"	16"	16"
Gate	2 x 2 Tube, Mesh Covered, Full Width Spring Assist Ramp Gate with Handle					



ST TUBE TOP UTILITY - TANDEM AXLE



Tube Top Rail and Uprights



10K MODELS

INCLUDE 7K SET-BACK JACK, 3X2 TUBE TOP RAIL AND LADDER REINFORCED GATE

TUBE TOP UTILITY - TANDEM AXLE STANDARD FEATURES

15" Radial Tires (205 75R15 LRC) 3.5k Axle
15" Radial Tires (225 75R15 LRD) 5k Axle
Easy Lube Hubs
2 x 2 Heavy Tube Top Rail for Structural Rigidity
Tube Uprights
2K, Zinc Plated Set-Back Jack

Tread Plate Fenders
Spare Tire Mount
Bead Blasted, Iron Phosphate Washed
Powder Coat Finish
Fold Flat Ramp Gate with Handle
Spring Assisted Rear Ramp Gate

Self-Retained Gate Pins
Pressure Treated 2 x 6 Decking
Front and Rear Board Retainers
Wiring Enclosed In Tubular Steel
Sealed LED Lighting

SPECIFICATIONS

	7' x 14' (7K)	7' x 16' (7K)	7' x 18' (7K)	7' x 20' (7K)	7' x 16' (10K)	7' x 18' (10K)	7' x 20' (10K)
Model #	ST8214TAT-B-070	ST8216TAT-B-070	ST8218TAT-B-070	ST8220TAT-B-070	ST8216TAT-B-100	ST8218TAT-B-100	ST8220TAT-B-100
GVWR (lb. / Axle)	7000	7000	7000	7000	9900	9900	9900
GAWR (lb. / Axle)	3500	3500	3500	3500	5200	5200	5200
Curb Weight	1700	1820	2200	2410	2530	2650	2770
Payload	5300	5180	4800	4590	7370	7250	7130
Frame	3" x 2" x 1/4" Angle		4" x 3" x 1/4" Angle		5" x 3" x 1/4" Angle		
Cross Members	3 x 2 x 3/16 Angle (24" On-Center)						
Top Rail	2" x 2" Square Tube				3" x 2" Tube		
Tongue	4" Channel (A-Frame)				5" Channel (A-Frame)		
Uprights	2" x 2" square Tube						
Coupler	2-5/16" Ball						
Jack	2K Zinc Plated, Set Back				7K Dropleg		
Fenders	Tread Plate, Double Brake						
Easy Lube Axles	Cambered Brake (Both Axles)				Cambered Brake (Both Axles)		
Suspension	Equalized Leaf Spring						
Tires	205/75R15 LRC				225/75R 15 LRD		
Wheels	15", 5 on 4.5, Radial Tires				15", 6 on 5.5, Radial Tires		
Decking	2 x 6 Pressure Treated Pine						
Lights	All LED Lights						
Electric Plug	7 Pole RV Molded Flat Blade						
Finish	Powder Coated High Gloss Black						
Overall Length	215"	239"	263"	287"	239"	263"	287"
Bed Length	168"	192"	216"	240"	192"	216"	240"
Bed Width	81.5"	81.5"	81.5"	81.5"	81.5"	81.5"	81.5"
Deck Height	18"	18"	18"	18"	19.5"	19.5"	19.5"
Coupler Height	16"	16"	16"	16"	17"	17"	17"
Gate	2 x 2 Tube, Mesh Covered, Full Width Spring Assist Ramp Gate with Handle				Reinforced (Ladder Style)		

