



STANDARD DUTY FLATBED DECKOVER

		8.5 x 18	8.5 x 20	8.5 x 22
Model #	Bumper Pull	ST10218SDDO-B-150	ST10220SDDO-B-150	ST10222SDDO-B-150
	Gooseneck	ST10218SDDO-GN-150	ST10220SDDO-GN-150	ST10222SDDO-GN-150
GVWR (lbs)		15000	15000	15000
GAWR (lbs/axle)		7000	7000	7000
Curb Weight	Bumper Pull	2685	3070	3457
	Gooseneck	3490	3870	4257
Payload	Bumper Pull	12315	11930	11543
	Gooseneck	11510	11130	10743
Main Frame		W10 x 12#/ft., I-Beam		
Side Rails		5" C-Channel		
Cross Members		3" C-Channel (16" On-Center)		
Coupler	Bumper Pull	Adjustable 2-5/16" Ball Coupler		
	Gooseneck	Adjustable 2-5/16" Gooseneck Coupler		
Jack	Bumper Pull	Setback HD 12K Drop Leg Jack		
	Gooseneck	Dual Setback HD 12K Drop Leg Jacks with Toolbox (Between Uprights), Tool Tray and Winch Receiver Tube (In Neck)		
Axles		Easy Lube Hubs with Brakes		
Suspension		Slipper Spring		
Tires		235/80R16 LRE		
Wheels		16", 8 on 6.5, Radial		
Decking		2 x 6 Pressure Treated Pine		
Lights		All LED Lights		
Electric Plug		7-Way RV-Style Molded Plug		
Finish		Powder Coated High Gloss Black		
Overall Length	Bumper Pull	275"	299"	323"
	Gooseneck	323"	347"	371"
Deck Height		36"	36"	36"
Coupler Height	Bumper Pull	Adjustable 21"-29"		
	Gooseneck	Adjustable 31" - 39-3/4"		

STANDARD DUTY FLATBED DECKOVER FEATURES

HD I-Beam Frame HD Tube Bulkhead Adjustable 2-5/16" Coupler Safety Chains 7-Way RV-Style Molded Plug Breakaway Switch with Battery EverLink™ Wiring Harness	Sealed Brake Connections Setback HD 12K Drop Leg Jack HD Slipper Spring Axles Brakes on Both Axles Easy Lube Hubs 16" Radial Tires Silver Wheels	Wheel Assembly, 235 80R16 LRE Powder Coat Finish 2" x 6" Pressure Treated Decking (6) 1/2" D-rings Stake Pockets and Rub Rail Adjustable Spare Tire Carrier All LED Lights
---	--	--

