

ST AIR BRAKE DECKOVER



Heavy Duty Suspension



AIR BRAKE DECKOVER FEATURES

215/75R17.5 LRH Tires
 66K Pintle Eye
 Dual 50K 2-Speed Jacks
 Safety Chains (5/8" High Test)
 Heavy Duty Suspension
 Oil-Bath Axles
 Hi-Tensile Steel Construction

Full Pierced Beam Construction
 Steel Plated Tongue
 Fabricated Bulkhead
 Step On-Tongue (Driver's Side)
 (12) 1" D-Rings
 Lockable Toolbox In-Tongue
 Spare Tire Carrier

Cleated Wheel Covers
 5' Bi-Directional, Fold Flat Spring-Assisted Wood-Filled Ramps
 Powder Coat Finish
 2" Nominal Oak Decking
 Mud Flaps
 Sealed LED Lighting
 Everlink™ - High Performance Wiring Harness

SPECIFICATIONS

| | 8.5' x 20' + 5' (49K) | 8.5' x 24' + 5' (61K) |
|----------------|--|------------------------------|
| Model # | ST102205ABD02A-B-490 | ST102245ABD03A-B-610 |
| GVWR (lb.) | 49000 | 61000 |
| GAWR (lb.axle) | 20000 | 20000 |
| Curb Weight | 9450 | 11300 |
| Payload | 39550 | 49700 |
| Main Frame | W14 x 22#/ft. I-Beam | W14 x 26#/ft. I-Beam |
| Side Rails | 8" C-Channel Side Rails | |
| Cross Members | 6" Jr-I-Beam (16" On Ctr) | |
| Tongue | Steel Plated Tongue, 72" Length | |
| Beaver Tail | 13 Degree, 60" Length | |
| Coupler | 66K Pintle Eye | |
| Jack | Dual 50K 2-Speed Jacks (Bolt-On) | |
| Axles | Oil-Bath Axles | Oil-Bath Axles (Triple Axle) |
| Suspension | Heavy Duty Suspension | |
| Tires | 215/75R17.5 LRH Tires | 215/75R17.5 LRH Tires |
| Wheels | 17.5", 8 on 6.5, Radial | 17.5", 8 on 6.5, Radial |
| Decking | 2" Nominal Oak Decking | |
| Lights | All LED Lights | |
| Electric Plug | 7-Way Cold Temperature Semi-Style Plug | |
| Finish | Powder Coat High Gloss Black | |
| Overall Length | 378" | 426" |
| Deck Height | 34-1/4" | 34-1/4" |
| Coupler Height | Adjustable 21"-29" | |

