

ST RACING PRO



Standard Features

Height

- 7' Interior Height

Frame

- 6x2 Tube Frame and Tongue
- 16" On-Center Tube Wall Studs
- 16" On-Center C-Channel Floor Crossmembers
- 6" Extended Triple-Tube Tongue
- 16" On-Center Tube Roof Bows
- 48" Beavertail (24" on 16' unit)

Hitch

- 7-Way Molded Plug
- Adjustable 2-5/16" Coupler
- 7K Setback Jack
- Safety Chains

Axle

- Torsion Axles with 12" Spread with Individual Fender Flares
- All Wheel Brakes

Wheels/Tires

- Easy Lube Hubs
- Radial Tires on Aluminum Wheels (up to 14K)

Interior

- White Vinyl Walls
- White Ceiling
- (4) 6K D-Rings
- 3/4" Engineered Wood Flooring

12 Volt Electrical

- (2) High Output Rectangular Dome Lights w/ 3-Way Switch
- (4) Slimline LED Stop, Tail, Turn Tail Lights w/ ***Integrated Backup Lights**

Exterior

- .030 Smooth Aluminum Exterior
- Screw-less Exterior
- Polished BullNose Cast Coners
- Bright Front Corners
- Bright Rear Hoop
- 24" Stoneguard w/Top Trim
- Seamless Aluminum Roof w/ 3" Top Trim
- 12" Rear Spoiler with Loading Light
- 3" Bottom Trim
- Rubberized Undercoating
- Polyethylene Vapor Barrier
- Flow-Through Scoop Vents

Door

- 48"x70" RV Side Door w/Aluminum Door Holder and Step Well
- 4" Wide Door Posts for max. opening width (2" Wider than std)
- 4100 lb. Rated Heavy-Duty Rear Ramp Door w/ Nu-Poly Flap
- 1/4 Turn Die-Cast Paddle Latches (In Lieu of Bar-Locks)

Deluxe Model Includes:

- Rubber Treadplate Flooring
- Upper and Lower Front Cabinet with Countertop (Cabinet Color to Match Exterior of Trailer)
- (4) High Output Rectangular Dome Lights
- 36" Aluminum Pull-Out Step
- Additional Marker Lights on side, and (3) Amber LED Eyebrow Lights
- Battery and Trickle Charger

Limited 3-Year Warranty

* Denotes New for 2020

SPECIFICATIONS

		10K	14K	10K (Deluxe)	14K (Deluxe)
Model #	20'	STBNRP10220TA-100	STBNRP10220TA-140	STBNRPD10220TA-100	STBNRPD10220TA-140
	24'	STBNRP10224TA-100	STBNRP10224TA-140	STBNRPD10224TA-100	STBNRPD10224TA-140
	28'	STBNRP10228TA-100	STBNRP10228TA-140	STBNRPD10228TA-100	STBNRPD10228TA-140
	32'	STBNRP10232TA-100	STBNRP10232TA-140	STBNRPD10232TA-100	STBNRPD10232TA-140
GVWR (lb.)		9900	14000	9900	14000
GAWR (lb.axle)		5200	7000	5200	7000
Curb Weight	20'	4900	5440	4900	5440
	24'	5100	5640	5100	5640
	28'	5440	5960	5440	5960
	32'	6360	6880	6360	6880
Payload	20'	5000	8560	5000	8560
	24'	4800	8360	4800	8360
	28'	4460	8040	4460	8040
	32'	3540	7120	3540	7120
Frame		6 x 2, 1/8" Tube	6 x 2, 3/16" Tube	6 x 2, 1/8" Tube	6 x 2, 3/16" Tube
Cross Members		C-Channel (16" On-Center)	Tube (16" On-Center)	C-Channel (16" On-Center)	Tube (16" On-Center)
Tongue		6 x 2, 1/8" Tube	6 x 2, 3/16" Tube	6 x 2, 1/8" Tube	6 x 2, 3/16" Tube
Wall Studs		Tube (16" On-Center)			
Roof Bows		Tube (16" On-Center)			
Coupler		Adjustable 2 5/16" Ball			
Jack		7K Dropleg			
Fenders		Aluminum Teardrop			
Easy Lube Axles		Torsion (Includes 12" Spread)			
Tires		225/75R15 LRD	235/80R16 LRE	225/75R15 LRD	235/80R16 LRE
Wheels		15", 6 on 5.5, Radial	16", 8 on 6.5, Radial	15", 6 on 5.5, Radial	16", 8 on 6.5, Radial
Wheels		Aluminum			
Flooring		Engineered Wood		Rubber Tread Plate	
Lights		All LED Lights w/ Integrated Backup Lights			
Electric Plug		7 Pole RV Molded Flat Blade			
Exterior		.030 Aluminum			
Overall Length	20'	303"			
	24'	351"			
	28'	399"			
	32'	447"			
Overall Width		102"			
Overall Height		110"	112"	110"	112"
Interior Height		84"			
Interior Width / Between Fenders		97" / 80.5"			
Interior Length	20'	249"			
	24'	297"			
	28'	345"			
	32'	393"			
Floor Height		21"	23"	21"	23"
Rear Door Opening (WxH)		92" x 82.50"			
Ramp Door Capacity (lb.)		4100			

