



STANDARD DUTY LOW PROFILE DUMP



Adjustable Coupler



10K Models Include 7K Set-Back Jack

STANDARD DUTY LOW PROFILE DUMP FEATURES

15" Radial Tires (205 75R15 LRC) 3.5K Axle
15" Radial Tires (225 75R15 LRD) 5K Axle
Easy Lube Hubs
Straight Axle
All-Wheel Brakes
Sealed Brake Connections
2-5/16" A-Frame Coupler
2K, Zinc Plated Coupler Mounted Jack (7K)

7K Set-Back Jack (10K)
Welded Tubular Steel Main Frame
Integrated Side Body Stiffening System
Spare Tire Carrier
Stake Pockets - 2 Per Side
Ramps
Integrated Tarp Mount
HD Tread Plate Fenders

Combo Barn Door Spreader Gate with Camber
(5) 1/2" D-Rings
Tongue Mounted HD Control Box with Key Lock
Iron Phosphate Wash Steel Prep
Powder Coat Finish
Deep Cycle Marine Grade Battery
EverLink™ - High Performance Wiring Harness
7-Way RV-Style Electrical Plug

SPECIFICATIONS

	6' x 10' (7K)	6' x 10' (10K)	6' x 12' (10K)
Model #	ST7210D1R-B-070	ST7210D1R-B-100	ST7212D1R-B-100
GVWR	7000	9900	9900
GAWR	3500	5200	5200
Curb Weight	2785	2950	3100
Payload	4215	6950	6800
Frame	5 x 2 Tube		
Cross Members	4" C-Channel		
Tongue	A-Frame - 5 x 2 Tube		
Coupler	2 5/16" A-Frame		
Jack	2K Zinc Plated, Coupler Mounted	7K Dropleg, Set Back	
Fenders	Heavy Duty Tread Plate Double Brake		
Easy Lube Axle	Easy Lube, Cambered Brake Axles		
Suspension	Leaf Spring		
Tires	205/75R 15 LRC	225/75R15 LRD	
Wheels	15", 5 on 4.5, Radial	15", 6 on 5.5, Radial	
Decking	11 GA Smooth Steel		
Lights	All LED Lights		
Electric Plug	7 Pole RV Molded Flat Blade		
Finish	Powder Coated High Gloss Black		
Overall Length	174"	174"	201"
Bed Width Inside	72"	72"	72"
Bed Length Inside	120"	120"	144"
Side Wall Height	20"	20"	20"
Deck Height	27"	27"	27"
Coupler Height	18"	18"	18"
Gate	Combination Barn Door Spreader Gate with Cambar		
Hydraulic Hoist	3" Ram, Power Up, Power Down	4" Ramp, Power Up, Power Down	
Hydraulic Pump	2500 PSI	3000 PSI	3000 PSI
Battery	12V Deep Cycle, DP24		

