

ST HD LOW PROFILE POWER TILT DECKOVER BUMPER PULL



Electrical Plug



HD LOW PROFILE POWER TILT DECKOVER - BUMPER PULL FEATURES

16" Radial Tires (235 80R16 LRE,) 15K
17.5" Radial Tires (215 75R17.5 LRH) 17.6K
Adjustable Pintle Hitch
HD 12K Jack
HD Slipper Spring Axles
Easy Lube Hubs
Sealed Brake Connections

HD Bulkhead
(6) 5/8" D-Rings
HD Stake Pockets and Rub Rail
Chain Spools
Side Step
Spare Tire Carrier
Tongue Mounted HD Control Box

Powder Coat Finish
Deep Cycle Marine Grade Battery
Battery Charger, 110V
Treated Decking
Sealed LED Lighting
Everlink™ - High Performance Wiring Harness
Dual Hydraulics
15 Degree Loading Angle

SPECIFICATIONS

	8.5' x 22' (15K)	8.5' x 22' + 4' (15K)	8.5' x 22' (17.6K)	8.5' x 22' + 4' (17.6K)
Model #	ST10222DOT2A-B-150	ST102224DOT2A-B-150	ST10222DOT2A-B-176	ST102224DOT2A-B-176
GVWR (lb.)	15000		17600	
GAWR (lb.axle)	7000		8000	
Curb Weight	4485	5170	4825	5370
Payload	10515	9830	12775	12230
Main Frame	W10 x 12#/ft., I-Beam			
Side Rails	6 x 2, 3/16 Wall Tube			
Cross Members	3" C-Channel (16" On-Center)			
Coupler	Adjustable Pintle		Adjustable 4 Bolt Pintle	
Jack	HD 12K Dropleg			
Axles	E-Z Lube Electric Brake			
Suspension	Slipper Leaf Spring			
Tires	235/80R16 LRE		215/75R17.5 LRH LRH	
Wheels	16", 8 on 6.5, Radial		17.5", 8 on 6.5, Radial	
Decking	2" Pressure Treated Pine			
Lights	All LED Lights			
Electric Plug	7 Pole RV Molded Flat Blade			
Finish	Powder Coat High Gloss Black			
Overall Length	330"	378"	330"	378"
Deck Height	34"	34"	34"	34"
Coupler Height	Adjustable 21" - 29"			
Hydraulic Hoist	Dual Ram (Power Up / Power Down)			
Pump	3000 PSI Pump with Reservoir			
Battery	12V Deep Cycle, DP24			
Load Angle	15 Degrees			

