

ST HD LOW PROFILE TRI AXLE DUMP



Tri-Axle



HD LOW PROFILE TRI-AXLE DUMP FEATURES

- 16" Radial Tires (235 80R16 LRE,) 7K Axle
- HD Slipper Spring Axles
- Easy Lube Hubs
- All-Wheel Brakes
- Sealed Brake Connections
- HD I-Beam Gooseneck
- Dual 12K Heavy Duty Jacks
- Welded Tubular Steel Main Frame
- Underbody Secure Tool Storage
- HD Control Box with Key Lock

- Combo Barn Door Spreader Gate with Cambar
- Spare Tire Carrier
- Side Steps
- Integrated Side Body Stiffening System
- 10 Gauge Floor
- Ramps (Stored Underneath Bed)
- Stake Pockets - 5 Per Side
- (5) 1/2" D-Rings
- Stabilizer Jack Receivers (Jacks Optional)
- Integrated Tarp Mount

- Tarp Kit (Installed) (NEW)
- Iron Phosphate Wash Steel Prep
- Deep Cycle Marine Grade Battery
- Battery Charger, 110V
- 7-Way RV-Style Electrical Plug
- EverLink™ - High Performance Wiring Harness
- All LED Lighting
- Power Up, Gravity Down Hydraulics (Telescopic)
- 7-Way RV-Style Electrical Plug

SPECIFICATIONS

	82" x 16' (21K)	82" x 16' (48" Sides) (21K)
Model #	ST8216TLDD-GN-210	ST8216TLDD4-GN-210
GVWR (lb.)	21,000	
GAWR (lb.axle)	7,000	
Curb Weight	5440	6530
Payload	15560	14470
Frame	8 x 2 Tube	
Cross Members	3" Channel	
Sides	24"	48"
Gooseneck Coupler	Adjustable 2-5/16"	
Jack	Dual HD 12K Dropleg	
Fenders	Heavy Duty Tread Plate, Double Brake	
Easy Lube Axles	Easy Lube Cambered Brake	
Suspension	Slipper Spring	
Tires	235/80R16 LRE	
Wheels	16", 8 on 6.5, Radial	
Decking	10 ga. Smooth Steel	
Lights	All LED Lights	
Electric Plug	7 Pole RV Molded Flat Blade	
Finish	Powder Coated High Gloss Black	
Overall Length	259"	
Bed Length Inside	192"	
Bed Width Inside	82"	
Side Wall Height	24"	48"
Deck Height	32"	
Coupler Height	Adjustable 31" - 39.75"	
Gate	Combination Barn Door Spreader Gate with Cambar	
Hydraulic Hoist	Power Up, Gravity Down	
Hydraulic Pump	2500 PSI	
Battery	12V Deep Cycle, DP31	

