



# PRO SERIES ROUND TOP CAR HAULER



## Standard Features

### Height

- 6'6" Interior Height

### Frame

- 6x2 Tube Frame and Tongue
- 16" On-Center Tube Wall Studs
- 16" On-Center C-Channel Floor Crossmembers
- Triple-Tube Tongue
- 24" On-Center Tube Roof Bows
- 48" Beavertail (24" on 16' unit)

### Hitch

- 7-Way Molded Plug
- 2-5/16" Coupler on 7K and 10K
- Adjustable 2-5/16" Coupler on 14K
- Safety Chains
- Zinc-Plated Setback Jack on 7K
- 7K Setback Jack on 10K & 14K

### Axle

- **\*Torsion Axles**
- All Wheel Brakes

### Wheels/Tires

- Easy Lube Hubs
- Radial Tires on Aluminum Wheels (up to 14K)

### Interior

- 3/8 Inch Plywood Wall Liner w/Aluminum H-Trim (Eliminates Stapled Luan Trim)
- 3/4" Engineered Wood Flooring
- (4) 6K D-Rings
- Thermo-Sheath® Ceiling Liner (Above Roof Bows)

### 12 Volt Electrical

- (2) 12 Volt Wall Mounted LED Dome Light (380 Lumens) w/1 Wall Switch LED 6" Oval Tail Lights
- w/Rubber mounted 3/4" Bullet Marker Lights (All Clear Lens)
- **\*Integrated Backup Lights**

### Exterior

- .030 Smooth Aluminum Exterior
- Screw-less Exterior
- Bright Front Corners
- Bright Rear Hoop
- 24" Stoneguard w/Top Trim
- .080 Aluminum Roof Cove w/Seamless Aluminum Roof
- 3" Bottom Trim
- Aluminum Fenders
- Rubberized Undercoating
- Polyethylene Vapor Barrier
- Flow-Through Scoop Vents

### Door

- 48"x70" RV Side Door w/Aluminum Door Holder and Step Well
- 4100 lb. Rated Heavy-Duty Rear Ramp Door w/Wood Flap

## Limited 3-Year Warranty

\* Denotes New for 2020

# SPECIFICATIONS

|                                  |                                            | 7K            | 10K                   | 14K                     |
|----------------------------------|--------------------------------------------|---------------|-----------------------|-------------------------|
| Model #                          | 18'                                        | STRCH10218TA  | STRCH10218TA-100      | STRCH10218TA-140        |
|                                  | 20'                                        | STRCH10220TA  | STRCH10220TA-100      | STRCH10220TA-140        |
|                                  | 24'                                        | STRCH10224TA  | STRCH10224TA-100      | STRCH10224TA-140        |
|                                  | 28'                                        | STRCH10228TA  | STRCH10228TA-100      | STRCH10228TA-140        |
| GVWR (lb.)                       |                                            | 7000          | 9900                  | 14000                   |
| GAWR (lb.axle)                   |                                            | 3500          | 5200                  | 7000                    |
| Curb Weight                      | 18'                                        | 3250          | 3450                  | 4155                    |
|                                  | 20'                                        | 3425          | 3600                  | 4330                    |
|                                  | 24'                                        | 3900          | 3900                  | 4650                    |
|                                  | 28'                                        | 4375          | 4325                  | 4975                    |
| Payload                          | 18'                                        | 3750          | 6450                  | 9845                    |
|                                  | 20'                                        | 3575          | 6300                  | 9670                    |
|                                  | 24'                                        | 3100          | 6000                  | 9350                    |
|                                  | 28'                                        | 2625          | 5575                  | 9025                    |
| Frame                            | 6x2, 1/8" Tube                             |               |                       | 6 x 2, 3/16" Tube       |
| Cross Members                    | C-Channel (16" On-Center)                  |               |                       | Tube (16" On-Center)    |
| Tongue                           | 6x2, 1/8" Tube                             |               |                       | 6 x 2, 3/16" Tube       |
| Wall Studs                       | Tube (16" On-Center)                       |               |                       |                         |
| Roof Bows                        | Tube (24" On-Center)                       |               |                       | Tube (16" On-Center)    |
| Coupler                          | 2 5/16" Ball                               |               |                       | Adjustable 2-5/16" Ball |
| Jack                             | 2K Set-Back Jack                           |               | 7K Dropleg            |                         |
| Fenders                          | Aluminum Teardrop                          |               |                       |                         |
| Easy Lube Axles                  | 22.5 Degree Up Torsion                     |               |                       |                         |
| Tires                            | 205/75R 15 LRC                             |               | 225/75R15 LRD         |                         |
| Wheels                           | 15", 5 on 4.5, Radial                      |               | 15", 6 on 5.5, Radial |                         |
| Wheels                           | 16", 8 on 6.5, Radial                      |               |                       |                         |
| Flooring                         | Aluminum                                   |               |                       |                         |
| Lights                           | Engineered Wood                            |               |                       |                         |
| Electric Plug                    | All LED Lights w/ Integrated Backup Lights |               |                       |                         |
| Exterior                         | 7 Pole RV Molded Flat Blade                |               |                       |                         |
| Overall Length                   | 18'                                        | .030 Aluminum |                       |                         |
|                                  | 20'                                        | 273"          |                       |                         |
|                                  | 24'                                        | 297"          |                       |                         |
|                                  | 28'                                        | 345"          |                       |                         |
| Overall Width                    | 97" / 80.5"                                |               |                       | 393"                    |
| Overall Height                   | 101"                                       |               | 101"                  |                         |
| Interior Height                  | 81"                                        |               |                       |                         |
| Interior Width / Between Fenders | 97" / 80.5"                                |               |                       |                         |
| Interior Length                  | 18'                                        | 225"          |                       |                         |
|                                  | 20'                                        | 249"          |                       |                         |
|                                  | 24'                                        | 297"          |                       |                         |
|                                  | 28'                                        | 345"          |                       |                         |
| Floor Height                     | 21"                                        |               | 21"                   |                         |
| Rear Door Opening (WxH)          | 90" x 76.50"                               |               |                       | 23"                     |
| Ramp Door Capacity (lb.)         | 4100                                       |               |                       |                         |

