

ST STANDARD DUTY BEAVERTAIL DECKOVER



Beavertail & Ramps



Gooseneck Models Include
I-Beam Gooseneck, Dual 12K Jacks, and Toolbox.

STANDARD DUTY BEAVERTAIL DECKOVER FEATURES

16" Radial Tires (235 80R16 LRE) 15K
Adjustable 2-5/16" Ball
HD 12K Jack
HD Slipper Spring Axle
Sealed Brake Connections
Easy Lube Hubs

Tube Constructed Bumper
HD Bulkhead
Multi-Position Spare Tire Carrier
(8) 5/8" D-Rings
HD Stake Pockets and Rub Rail
HD 4" Channel Stand Up Ramps

Powder Coat Finish
Treated Decking
Sealed LED Lighting
Everlink™ - High Performance Wiring Harness

SPECIFICATIONS

		8.5' x 18' + 4' (15K)	8.5' x 20' + 4' (15K)	8.5' x 22' + 4' (15K)
Model #	Bumper Pull	ST102184SDDO-B-150	ST102204SDDO-B-150	ST102224SDDO-B-150
	Gooseneck	ST102184SDDO-GN-150	ST102204SDDO-GN-150	ST102224SDDO-GN-150
GVWR (lb. / Axle)		15000	15000	15000
GAWR (lb. / Axle)		7000	7000	7000
Curb Weight	Bumper Pull	3130	3475	3825
	Gooseneck	3930	4275	4625
Payload	Bumper Pull	11870	11525	11175
	Gooseneck	11070	10725	10375
Main Frame		W10 x 12#/ft., I-Beam		
Side Rails		5" C-Channel		
Cross Members		3" C-Channel (16" On-Center)		
Coupler	Bumper Pull	Adjustable 2-5/16"		
	Gooseneck	Adjustable 2-5/16"		
Jack	Bumper Pull	HD 12K Dropleg		
	Gooseneck	Dual HD 12K Jacks with Toolbox		
Axles		Cambered Brake Both Axles		
Suspension		Slipper Spring		
Tires		235/80R16 LRE		
Wheels		16", 8 on 6.5, Radial		
Decking		2" Pressure Treated Pine		
Lights		All LED Lights		
Electric Plug		7 Pole RV Molded Flat Blade		
Finish		Powder Coated High Gloss Black		
Overall Length	Bumper Pull	323"	347"	371"
	Gooseneck	371"	395"	419"
Coupler Height	Bumper Pull	Adjustable 21" - 29"		
	Gooseneck	Adjustable 31" - 39.75"		
Ramps		5ft. 4" HD Channel Stand-Up, Spring-Assist		
Deck Height		36"	36"	36"

