

ST STANDARD DUTY FLATBED DECKOVER



Rear Bumper



**Gooseneck Models Include
I-Beam Gooseneck, Dual 12K Jacks, and Toolbox.**

STANDARD DUTY FLATBED DECKOVER FEATURES

15" Radial Tires (225 75R15 LRD) 5K Axle
Adjustable 2-5/16" Coupler
7K Dropleg Jack
Eye-To-Eye Spring Axle
Easy Lube Hubs
Sealed Brake Connections

HD Bulkhead
(6) 1/2" D-Rings
Stake Pockets and Rub Rail
Diamond Plate Wheel Covers
Multi-Position Spare Tire Carrier
HD 4" Channel Stand Up Ramps

Spring-Assisted Ramps
Powder Coat Finish
32" Deck Height
Pressure Treated 2 x 6 Decking
Sealed LED Lighting
EverLink™ - High Performance Wiring Harness

SPECIFICATIONS

| | | 8.5' x 18' (15K) | 8.5' x 20' (15K) | 8.5' x 22' (15K) |
|----------------|-------------|--------------------------------|--------------------|--------------------|
| Model # | Bumper Pull | ST10218SDDO-B-150 | ST10220SDDO-B-150 | ST10222SDDO-B-150 |
| | Gooseneck | ST10218SDDO-GN-150 | ST10220SDDO-GN-150 | ST10222SDDO-GN-150 |
| GVWR (lb.) | | 15000 | 15000 | 15000 |
| GAWR (lb.axle) | | 7000 | 7000 | 7000 |
| Curb Weight | Bumper Pull | 2685 | 3070 | 3457 |
| | Gooseneck | 3485 | 3870 | 4257 |
| Payload | Bumper Pull | 12315 | 11930 | 11543 |
| | Gooseneck | 11515 | 11130 | 10743 |
| Main Frame | | W10 x 12#/ft., I-Beam | | |
| Side Rails | | 5" C-Channel | | |
| Cross Members | | 3" C-Channel (16" On-Center) | | |
| Coupler | Bumper Pull | Adjustable 2-5/16" | | |
| | Gooseneck | Adjustable 2-5/16" | | |
| Jack | Bumper Pull | HD 12K Dropleg | | |
| | Gooseneck | Dual HD 12K Jacks with Toolbox | | |
| Axles | | Cambered Brake Both Axles | | |
| Suspension | | Slipper Spring | | |
| Tires | | 235/80R16 LRE | | |
| Wheels | | 16", 8 on 6.5, Radial | | |
| Decking | | 2" Pressure Treated Pine | | |
| Lights | | All LED Lights | | |
| Electric Plug | | 7 Pole RV Molded Flat Blade | | |
| Finish | | Powder Coated High Gloss Black | | |
| Overall Length | Bumper Pull | 275" | 299" | 323" |
| | Gooseneck | 323" | 347" | 371" |
| Coupler Height | Bumper Pull | Adjustable 21"-29" | | |
| | Gooseneck | Adjustable 31" - 39-3/4" | | |
| Deck Height | | 36" | 36" | 36" |

