

ST TUBE TOP 3-BOARD HIGH SIDE



3-Board High Side D-Rings



TUBE TOP 3-BOARD HIGH SIDE STANDARD FEATURES

15" Radial Tires (205 75R15 LRC) 3.5K Axle
Easy Lube Hubs
2K, Zinc Plated Set-Back Jack
2x2 Heavy Tube Top Rail (Structural Rigidity)
Tube Uprights
Tread Plate Fenders

Spare Tire Carrier
5/4 Treated Lumber Sides and Front
Sealed LED Lighting
(4) 1/2" D-Rings
Bead Blasted, Iron Phosphate Washed
Powder Coat Finish

Fold Flat Ramp Gate with Handle
Spring-Assisted Rear Ramp Gate
Self-Retained Gate Pins
Pressure Treated 2 x 6 Decking
Front and Rear Board Retainers
Wiring Enclosed in Tubular Steel

SPECIFICATIONS

	5' x 8' (3K)	5' x 10' (3K)	6' x 10' (3K)	6' x 12' (3K)	7' x 12' (3K)	7' x 14' (7K)	7' x 16' (7K)
Model #	ST6208HST-B-030	ST6210HST-B-030	ST7210HST-B-030	ST7212HST-B-030	ST8212HST-B-030	ST8214HST-B-070	ST8216HST-B-070
GVWR	2990	2990	2990	2990	2990	7000	7000
GAWR	3500	3500	3500	3500	3500	3500	3500
Curb Weight	990	1170	1230	1300	1430	2040	2210
Payload	2000	1820	1760	1690	1560	4960	4790
Frame	3 x 2 x 3/16 Angle					3 x 2 x 1/4 Angle	
Cross Members	3 x 2 x 3/16 Angle (24" On-Center)						
Top Rail	2 x 2 Square Tube						
Tongue	3" Channel (A-Frame)					4" Channel (A-Frame)	
Uprights	2 x 2 Square Tube						
Coupler	2" Ball					2 5/16" Ball	
Jack	2K Zinc Plated, Set Back						
Fenders	Tread Plate, Square Rolled					Tread Plate, Double Brake	
Easy Lube Axles	Cambered Idler with Brake Flange					Cambered Brake (Both Axles)	
Suspension	Leaf Spring					Equalized Leaf Spring	
Tires	205/75R15 LRC						
Wheels	15", 5 on 4.5, Radial Tire						
Decking	2 x 6 Pressure Treated Pine						
Lights	All LED Lights						
Electric Plug	4 Way Flat					7 Pole RV Molded Flat Blade	
Finish	Powder Coated High Gloss Black						
Overall Length	137"	161"	161"	185"	185"	209"	233"
Bed Length	96"	120"	120"	144"	144"	168"	192"
Bed Width	59.5"	59.5"	69.5"	69.5"	79.5"	79.5"	79.5"
Deck Height	18"	18"	18"	18"	18"	18"	18"
Coupler Height	16"	16"	16"	16"	16"	16"	16"
Gate	2 x 2 Tube, Mesh Covered, Full Width Spring-Assist Ramp Gate with Handle						

