

ST TUBE TOP ATV



Spare Tire Mount



TUBE TOP ATV STANDARD FEATURES

15" Radial Tires (205 75R15 LRC) 3.5K Axle
Easy Lube Hubs
2K, Zinc Plated Set-Back Jack
2 x 2 Heavy Tube Top rail for Structural Rigidity
Tube Uprights
Tread Plate Fenders

Stake Pockets
Spare Tire Carrier
Bead Blasted, Iron Phosphate Washed Bead
Powder Coat Finish
Fold Flat Ramp Gate with Handle
Spring-Assisted Rear Ramp Gate

Self-Retained Gate Pins
Front and Rear Board Retainers
Wiring Enclosed in Tubular Steel
Pressure Treated 2 x 6 Decking
Sealed LED Lighting
5ft Fabricated Steel Ramps (Side Storing)

SPECIFICATIONS

	6' x 12' (3K)	7' x 12' (3K)	7' x 14' SA (3K)	7' x 14' TA (7K)	7' x 16' (7K)
Model #	ST7212TATV-B-030	ST8212TATV-B-030	ST8214TATV-B-030	ST8214TATTV-B-070	ST8216TATTV-B-070
GVWR (lb.)	2990	2990	2990	7000	7000
GAWR (lb.axle)	3500	3500	3500	3500	3500
Curb Weight	1320	1370	1450	1740	1910
Payload	1670	1620	1540	5260	5090
Frame	3 x 2 x 3/16 Angle			3 x 2 x 1/4 Angle	
Cross Members	3 x 2 x 3/16 Angle (24" On-Center)				
Top Rail	2 x 2 Square Tube				
Tongue	3" Channel (A-Frame)			4" Channel (A-Frame)	
Uprights	2 x 2 Square Tube				
Coupler	2" Ball			2-5/16" Ball	
Jack	2K Zinc Plated, Set Back				
Fenders	Tread Plate, Square Rolled			Tread Plate, Double Brake	
Easy Lube Axles	Cambered Idler with Brake Flange			Cambered Brake (Both Axles)	
Suspension	Leaf Spring			Equalized Leaf Spring	
Tires	205/75R15 LRC				
Wheels	15", 5 on 4.5				
Decking	2 x 6 Pressure Treated Pine				
Lights	All LED Lights				
Electric Plug	4 Way Flat			7 Pole RV Molded Flat Blade	
Finish	Powder Coated High Gloss Black				
Overall Length	185"	185"	209"	209"	237"
Bed Length	144"	144"	168"	168"	192"
Bed Width	71.5"	81.5"	81.5"	81.5"	81.5"
Deck Height	18"	18"	18"	18"	18"
Coupler Height	16"	16"	16"	16"	16"
Gate	2 x 2 Tube, Mesh Covered, Full Width Spring-Assist Ramp Gate with Handle				

