



Shown with Optional HD I-Beam Gooseneck





SURE-TRAC DIFFERENCE

HD Bulkhead HD 12K Dropleg Jack Slipper Spring Suspension Multi-Position Spare Tire Carrier Everlink ™ - High Performance Wiring Harness HD 4" Channel Ramps

FEATURES

2 x 6 Pressure Treated Decking 16" Radial Tires Tube Constructed Bumper HD Stake Pockets and Rub Rail (8) 5/8" D-Rings Adjustable 2-5/16" Ball Sealed Brake Connections Sealed LED Lighting Powder Coat Finish

OPTIONS

Gooseneck Spare Tire Oak Deck Color Options

Contact Local Dealer For More Options









SMART - CONFIDENT - PROVEN

SD BEAVERTAIL DECKOVER SPECIFICATIONS

		8.5 x 18 + 4	8.5 x 20 + 4	8.5 x 22 + 4
GVWR (lbs)		15000	15000	15000
GAWR (lbs/axle)		7000	7000	7000
Curb Weight	Bumper Pull	2685	3070	3457
	Gooseneck	3485	3870	4257
Payload	Bumper Pull	12315	11930	11543
	Gooseneck	11515	11130	10743
Main Frame		W10 x 12#/ft., I-Beam		
Side Rails		5" C-Channel		
Cross Members		3" C-Channel (16" On-Center)		
Coupler	Bumper Pull	Adjustable 2-5/16"		
	Gooseneck	Adjustable 2-5/16"		
Jack	Bumper Pull	HD 12K Dropleg		
	Gooseneck	Dual HD 12K Jacks with Toolbox		
Axles		Cambered Brake Both Axles		
Suspension		Slipper Spring		
Tires		235/80R16 LRE		
Wheels		16", 8 on 6.5, Radial		
Decking		2" Pressure Treated Pine		
Lights		All LED Lights		
Electric Plug		7 Pole RV Molded Flat Blade		
Finish		Powder Coated High Gloss Black		
Overall Length	Bumper Pull	323"	347"	371"
	Gooseneck	371"	395"	419"
Deck Height		36"	36"	36"
Coupler Height	Bumper Pull	Adjustable 21" - 29"		
	Gooseneck	Adjustable 31" - 39.75"		
Ramps		5ft. 4" HD Channel Stand-Up, Spring Assist		







