

ST ALUMINUM COMPOSITE SIDE

	SA 5' x 8'	SA 5' x 10'	SA 6' x 10'	SA 6' x 12'	SA 7' x 12'
Model #	C6208CWS-A-030	C6210CWS-A-030	C7210CWS-A-030	C7212CWS-A-030	C8212CWS-A-030
GVWR (lbs)	2990	2990	2990	2990	2990
GAWR (lbs/axle)	3500	3500	3500	3500	3500
Curb Weight	605	625	700	755	810
Payload	2385	2365	2290	2235	2180
Frame	3 x 2 x 3/16 Angle				
Cross Members	3 x 2 x 3/16 Angle				
Top Rail	2 x 2 Square Tube				
Tongue	4 x 2 Tube				
Uprights	2 x 2 Square Tube				
Coupler	2" A-Frame Coupler				
Jack	1K Swivel Jack with Caster Wheel				
Fenders	Square Rolled with Backer				
Easy Lube Axles	Cambered Idler with Brake Flange				
Suspension	Leaf Spring				
Tires	205/75R15 LRC				
Wheels	15", 5 on 4.5, Radial Tires				
Decking	1/8" Extruded Aluminum Flooring				
Lights	All LED Lights				
Electric Plug	4-Way Flat Molded Plug				
Finish	Aluminum				
Overall Length	147"	171"	171"	195"	195"
Bed Length	96"	120"	120"	144"	144"
Bed Width	61.5"	61.5"	71.5"	71.5"	81.5"
Deck Height	18"	18"	18"	18"	18"
Coupler Height	16"	16"	16"	16"	16"
Gate	Bi-Fold Aluminum Gate				

ALUMINUM COMPOSITE SIDE STANDARD FEATURES

3" x 2" x 3/16" Aluminum Angle Frame	4-Way Flat Molded Plug	Aluminum Wheels
4" x 2" Aluminum Tube Tongue	1K Swivel Jack with Caster Wheel	Wheel Assembly, 205 75R15 LRC
2" x 2" Tube Top Rail	54" Bi-Fold Aluminum Ramp Gate	Extruded Aluminum Flooring
Tube Uprights	Aluminum Fenders	(4) Recessed D-rings
Composite Wood Sides	Idler Axle	Stake Pockets
2" A-Frame Coupler	Easy Lube Hubs	Spare Tire Carrier
Safety Chains	15" Radial Tires	All LED Lights

