



ALUMINUM EQUIPMENT

	7' x 16' + 2'	7' x 18' + 2'	7' x 20' + 2'	7' x 16' + 2'	7' x 18' + 2'	7' x 20' + 2'
Model #	C8218ET-A-100	C8220ET-A-100	C8222ET-A-100	C8218ET-A-140	C8220ET-A-140	C8222ET-A-140
GVWR	9900	9900	9900	14000	14000	14000
GAWR	5000	5000	5000	7000	7000	7000
Curb Weight	1430	1510	1590	1795	1945	2095
Payload	8470	8390	8310	12205	12055	11905
Frame	6" C-Channel			8" C-Channel		
Cross Members	3" Channel			4" Channel		
Tongue	6" Channel			6" Channel		
Coupler	2-5/16" A-Frame Coupler			Adjustable 2-5/16" Coupler		
Jack	Setback 7K Drop Leg Jack			Setback HD 12K Drop Leg Jack		
Fenders	Double Brake with Backer					
Easy Lube Axles	Cambered Brake (Both Axles)					
Suspension	Double Eye Leaf Spring			HD Slipper Spring		
Tires	225/75R15 LRD			235/80R16 LRE		
Wheels	15", 6 on 5.5			16", 8 on 6.5		
Decking	1/8" Extruded Aluminum Flooring					
Lights	All LED Lights					
Electric Plug	7-Way RV-Style Molded Plug					
Finish	Aluminum					
Overall length	262"	286"	310"	288"	312"	310"
Deck Length - Flat	192"	216"	240"	216"	240"	240"
Drop Tail Length	24"	24"	24"	48"	48"	24"
Between Fenders	82"	82"	82"	82"	82"	82"
Deck Height	26"	26"	26"	26"	26"	26"
Coupler Height	18"	18"	18"	18"	18"	18"
Ramps	Aluminum Standup Ramps					

ALUMINUM EQUIPMENT FEATURES

<ul style="list-style-type: none"> 6" C-Channel Frame (10K Models) 8" C-Channel Frame (14K Models) Full Wrapped C-Channel Tongue HD Tube Bulkhead 2-5/16" A-Frame Coupler (10K Model) Adjustable 2-5/16" Coupler (14K Models) Safety Chains 7-Way RV-Style Molded Plug EverLink™ Wiring Harness 	<ul style="list-style-type: none"> Sealed Brake Connections Setback 7K Drop Leg Jack (10K Models) Setback HD 12K Drop Leg Jack (14K Models) 2' Cleated Beavertail 5' Aluminum Standup Ramps HD Aluminum Fenders (Both Removable) Slipper Spring Suspension (14K Models) Easy Lube Hubs 	<ul style="list-style-type: none"> 15" Radial Tires (10K Models) 16" Radial Tires (14K Models) Aluminum Wheels Extruded Aluminum Flooring (4) Recessed D-rings Stake Pockets and Rub Rail Spare Tire Carrier All LED Lights
--	--	---

