

ST ALUMINUM LOW SIDE

	SA 7' x 10'	SA 7' x 12'	SA 7' x 14'
Model #	C8210LS-A-030	C8212LS-A-030	C8214LS-A-030
GVWR (lb.)	2990	2990	2990
GAWR (lb. / axle)	3500	3500	3500
Curb Weight	650	690	730
Payload	2340	2300	2260
Frame	5" Extrusion		
Top Rail	2 x 2 Square Tube		
Tongue	4 x 2 Tube		
Uprights	2 x 2 Square Tube		
Coupler	2" A-Frame Coupler		
Jack	1K Swivel Jack with Caster Wheel		
Fenders	Square Rolled with Backer		
Easy Lube Axles	Cambered Idler with Brake Flange		
Suspension	Torsion		
Tires	205/75R15 LRC		
Wheels	15", 5 on 4.5, Radial Tires		
Decking	1/8" Extruded Aluminum Flooring		
Lights	All LED Lights		
Electric Plug	4-Way Flat Molded Plug		
Finish	Aluminum		
Overall Length	164"	186"	208"
Bed Length	120"	144"	168"
Bed Width (Between Rails)	78"	78"	78"
Bed Width (Between Fenders)	82"	82"	82"
Deck Height	16 1/2"	16 1/2"	16 1/2"
Coupler Height	18"	18"	18"
Gate	Bi-Fold Aluminum Gate		

ALUMINUM LOW SIDE STANDARD FEATURES

5" x 3" Aluminum Extruded Frame 4" x 2" Aluminum Tube Tongue 2" A-Frame Coupler Safety Chains 4-Way Flat Molded Plug 1K Swivel Jack with Caster Wheel	54" Bi-Fold Aluminum Ramp Gate Aluminum Fenders 3500 lb. Torsion Axle Idler Axle Easy Lube Hubs 15" Radial Tires	Aluminum Wheels Wheel Assembly, 205 75R15 LRC Extruded Aluminum Flooring (4) D-rings Spare Tire Carrier All LED Lights
--	---	---

