



# HD LOW PROFILE POWER TILT - BUMPER PULL DECKOVER TRAILERS

	8.5 x 22, 15K	8.5 x 22+4, 15K	8.5 x 22, 17.6K	8.5 x 22+4, 17.6K
<b>Model #</b>	ST10222DOT2A-B-150	ST102224DOT2A-B-150	ST10222DOT2A-B-176	ST102224DOT2A-B-176
<b>GVWR (lbs)</b>	15000		17600	
<b>GAWR (lbs/axle)</b>	7000		8000	
<b>Curb Weight</b>	4485	5170	4825	5370
<b>Payload</b>	10515	9830	12775	12230
<b>Main Frame</b>	W10 x 12#/ft., I-Beam			
<b>Side Rails</b>	6 x 2, 3/16 Wall Tube			
<b>Cross Members</b>	3" C-Channel (16" On-Center)			
<b>Coupler</b>	Adjustable Pintle Eye		Adjustable 4-Bolt Pintle Eye	
<b>Jack</b>	Setback HD 12K Drop Leg Jack			
<b>Axles</b>	Easy Lube Hubs with Brakes		Oil Bath Hubs with Brakes	
<b>Suspension</b>	Slipper Leaf Spring			
<b>Tires</b>	235/80R16 LRE		215/75R17.5 LRH LRH	
<b>Wheels</b>	16", 8 on 6.5, Radial		17.5", 8 on 6.5, Radial	
<b>Decking</b>	2 x 6 Pressure Treated Pine			
<b>Lights</b>	All LED Lights			
<b>Electric Plug</b>	7-Way RV-Style Molded Plug			
<b>Finish</b>	Powder Coat High Gloss Black			
<b>Overall Length</b>	330"	378"	330"	378"
<b>Deck Height</b>	34"	34"	34"	34"
<b>Coupler Height</b>	Adjustable 21" - 29"			
<b>Hydraulic Hoist</b>	Dual Ram (Power Up / Power Down)			
<b>Pump</b>	3000 PSI Pump with Reservoir			
<b>Battery</b>	Group 24 Deep Cycle			
<b>Load Angle</b>	15 Degrees			

Additional configurations available. Contact your local dealer for more information.

## ADDITIONAL FEATURES

- HD Tube Bulkhead
- Safety Chains
- Breakaway Switch with Battery
- EverLink™ Wiring Harness
- Diamond Plate Deck Over Wheels
- (6) 5/8" D-Rings (8 on units with stationary deck)
- Chain Spools
- Stake Pockets and Rub Rail
- Spare Tire Carrier
- Side Steps
- Tongue Mounted HD Control Box with Key Lock
- Battery Charger, 110-Volt
- Limited 3-Year Warranty



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final details



# HD LOW PROFILE POWER TILT - GOOSENECK DECKOVER TRAILERS

	8.5 x 22, 15K	8.5 x 22+4, 15K	8.5 x 22, 17.6K	8.5 x 22+4, 17.6K
<b>Model #</b>	ST10222DOT2A-GN-150	ST102224DOT2A-GN-150	ST10222DOT2A-GN-176	ST102224DOT2A-GN-176
<b>GVWR (lbs)</b>	15000		17600	
<b>GAWR (lbs/axle)</b>	7000		8000	
<b>Curb Weight</b>	4775	5460	5115	5660
<b>Payload</b>	10225	9540	12485	11940
<b>Main Frame</b>	W10 x 12#/ft., I-Beam			
<b>Side Rails</b>	6 x 2, 3/16 Wall Tube			
<b>Cross Members</b>	3" C-Channel (16" On-Center)			
<b>Coupler</b>	Adjustable 2-5/16" Gooseneck Coupler			
<b>Jack</b>	Dual Setback HD 12K Drop Leg Jacks with Toolbox (Between Uprights), Tool Tray and Winch Receiver Tube (In Neck)			
<b>Axles</b>	Easy Lube Hubs with Brakes		Oil Bath Hubs with Brakes	
<b>Suspension</b>	Slipper Leaf Spring			
<b>Tires</b>	235/80R16 LRE		215/75R17.5 LRH LRH	
<b>Wheels</b>	16", 8 on 6.5, Radial		17.5", 8 on 6.5, Radial	
<b>Decking</b>	2 x 6 Pressure Treated Pine			
<b>Lights</b>	All LED Lights			
<b>Electric Plug</b>	7-Way RV-Style Molded Plug			
<b>Finish</b>	Powder Coat High Gloss Black			
<b>Overall Length</b>	378"	426"	378"	426"
<b>Deck Height</b>	34"	34"	34"	34"
<b>Coupler Height</b>	Adjustable 31" - 39-3/4"			
<b>Hydraulic Hoist</b>	Dual Ram (Power Up / Power Down)			
<b>Pump</b>	3000 PSI Pump with Reservoir			
<b>Battery</b>	Group 24 Deep Cycle			
<b>Load Angle</b>	15 Degrees			

Additional configurations available. Contact your local dealer for more information.

## ADDITIONAL FEATURES

- HD Tube Bulkhead
- Safety Chains
- Breakaway Switch with Battery
- EverLink™ Wiring Harness
- Sealed Brake Connections
- Diamond Plate Deck Over Wheels
- (6) 5/8" D-Rings (8 on unit with Stationary Deck)
- Chain Spools
- Stake Pockets and Rub Rail
- Spare Tire Carrier
- Side Steps
- Tongue Mounted HD Control Box with Key Lock
- Tool Tray and Winch Receiver Tube (In Neck)
- Battery Charger, 110-Volt
- Limited 3-Year Warranty



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final details