

		8.5 x 18+4	8.5 x 20+4	8.5 x 22+4
Model #	Bumper Pull	ST102184SDD0-B-150	ST102204SDDO-B-150	ST102224SDDO-B-150
	Gooseneck	ST102184SDD0-GN-150	ST102204SDDO-GN-150	ST102224SDDO-GN-150
GVWR (lbs)		15000	15000	15000
GAWR (lbs/axle)		7000	7000	7000
Curb Weight	Bumper Pull	3130	3475	3825
	Gooseneck	3930	4275	4625
Payload	Bumper Pull	11870	11525	11175
	Gooseneck	11070	10725	10375
Main Frame		W10 x 12#/ft., I-Beam		
Side Rails		5" C-Channel		
Cross Members		3" C-Channel (16" On-Center)		
Coupler	Bumper Pull	Adjustable 2-5/16" Ball Coupler		
	Gooseneck	Adjustable 2-5/16" Gooseneck Coupler		
Jack	Bumper Pull	Setback HD 12K Drop Leg Jack		
	Gooseneck	Dual Setback HD 12K Drop Leg Jacks with Toolbox (Between Uprights), Tool Tray and Winch Receiver Tube (In Neck)		
Axles		Easy Lube Hubs with Brakes		
Suspension		Slipper Spring		
Tires		235/80R16 LRE		
Wheels		16", 8 on 6.5, Radial		
Decking		2 x 6 Pressure Treated Pine		
Lights		All LED Lights		
Electric Plug		7-Way RV-Style Molded Plug		
Finish		Powder Coated High Gloss Black		
Overall Length	Bumper Pull	323"	347"	371"
	Gooseneck	371"	395"	419"
Deck Height		36"	36"	36"
Coupler Height	Bumper Pull	Adjustable 21" - 29"		
	Gooseneck	Adjustable 31" - 39.75"		
Ramps		5ft. 4" HD Channel Spring-Assist Standup Ramps with Adjustable Support Legs		

Additional configurations available. Contact your local dealer for more information.

ADDITIONAL FEATURES

HD Tube Bulkhead Safety Chains **Breakaway Switch with Battery** EverLink™ Wiring Harness Sealed Brake Connections 4' Beavertail (8) 1/2" D-Rings Stake Pockets and Rub Rail Adjustable Spare Tire Carrier Limited 3-Year Warranty



