MINUM 3-BOARD

LANDSCAPE & UTILITY

Safety Chains Aluminum Wheels 5/4 Treated Lumber Sides and Front Pressure Treated 2" x 6" Decking 1/2" D-Rings (4) Stake Pockets Spare Tire Carrier Limited 3-Year Warranty



	5 x 8 SA	5 x 10 SA	6 x 10 SA	6 x 12 SA	7 x 12 SA	7 x 14 SA	7x 14 TA	7 x 16 TA	
Model #	ST-UTWA6208-030	ST-UTWA6210-030	ST-UTWA7210-030	ST-UTWA7212-030	ST-UTWA8212-030	ST-UTWA8214-030	ST-UTWA8214-070	ST-UTWA8216-070	
GVWR (lbs)	2990	2990	2990	2990	2990	2990	7000	7000	
GAWR (lbs/axle)	3500	3500	3500	3500	3500	3500	3500	3500	
Curb Weight	955	1080	1130	1240	1290	1400	1835	1840	
Payload	2035	1910	1860	1750	1700	1590	5165	5160	
Frame	3 x 2 x 3/16 Angle								
Cross Members	3 x 2 x 3/16 Angle						3" Channel		
Top Rail	2 x 2 Square Tube								
Tongue	4 x 2 Tube						5 x 2 Tube		
Uprights	2 1/2" X 1 1/4" Rectangular Tube								
Coupler	2" A-Frame Ball Coupler						2-5/16" A-Frame Ball Coupler		
Jack	1K Swivel Jack with Caster Wheel						Setback 2K Zinc Plated Jack		
Fenders	Square Rolled with Backer						Teardrop with Backer		
Axle(s)	Easy Lube Hubs						Easy Lube Hubs with Brakes		
Suspension	Leaf Spring						Equalized Leaf Spring		
Tires	205/75R15 LRC								
Wheels	15", 5 on 4.5, Radial Tires								
Decking	2" x 6" Pressure Treated Pine								
Lights	All LED Lights								
Electric Plug	4-Way Flat Molded Plug						7-Way RV-Style Molded Plug		
Finish	Aluminum								
Overall Length	147"	171"	171"	195"	195"	219"	219"	249"	
Bed Length	96"	120"	120"	144"	144"	168"	168"	192"	
Bed Width	61.5"	61.5"	71.5"	71.5"	81.5"	81.5"	81.5"	81.5"	
Deck Height	18"	18"	18"	18"	18"	18"	18"	18"	
Coupler Height	16"	16"	16"	16"	16"	16"	16"	16"	
Gate		Alumimum Ramp Gate							

