IMINUM LOW SIDE

LANDSCAPE & UTILITY

Safety Chains Enclosed Wiring Aluminum Wheels (4) D-Rings Stake Pockets Spare Tire Carrier Limited 3-Year Warranty



	7 x 10	7 x 12	7 x 14
Model #	ST-LSA8210-030	ST-LSA8212-030	ST-LSA8214-030
GVWR (lbs)	2990	2990	2990
GAWR (lbs/axle)	3500	3500	3500
Curb Weight	650	690	730
Payload	2340	2300	2260
Frame	5" Extrusion		
Top Rail	2 x 2 Square Tube		
Tongue	4 x 2 Tube		
Uprights	2 x 1.5 Tube		
Coupler	2" Ball Coupler		
Jack	1K Swivel Jack with Caster Wheel		
Fenders	Square Rolled with Backer		
Axle	Easy Lube Hubs		
Suspension	Torsion		
Tires	205/75R15 LRC		
Wheels	15", 5 on 4.5, Radial Tires		
Decking	Extruded Floor		
Lights	All LED Lights		
Electric Plug	4-Way Flat Molded Plug		
Finish	Aluminum		
Overall Length	164"	186"	208"
Bed Length	120"	144"	168"
Bed Width	78"	78"	78"
Bed Width	82"	82"	82"
Deck Height	16 1/2"	16 1/2"	16 1/2"
Coupler Height	18"	18"	18"
Gate	Bi-Fold Aluminum Gate		

