

# HEAVY DUTY LOW PROFILE POWER TILT GOOSENECK DECKOVER

- HD Tube Bulkhead
- Safety Chains
- Breakaway Switch with Battery
- EverLink™ Wiring Harness
- Sealed Brake Connections
- Diamond Plate Deck Over Wheels
- (6) 5/8" D-Rings (8 on unit with Stationary Deck)
- Chain Spools
- Stake Pockets and Rub Rail
- Spare Tire Carrier
- Side Steps
- Tongue Mounted HD Control Box with Key Lock
- Tool Tray and Winch Receiver Tube (In Neck)
- Battery Charger, 110-Volt
- Limited 3-Year Warranty



	8.5 x 22, 15K	8.5 x 22+4, 15K	8.5 x 22, 17.6K	8.5 x 22+4, 17.6K
Model #	ST-DOT10222-150G	ST-DOT102224-150G	ST-DOT10222-176G	ST-DOT102224-176G
GVWR (lbs)	15000		17600	
GAWR (lbs/axle)	7000		8000	
Curb Weight	4775	5460	5115	5660
Payload	10225	9540	12485	11940
Main Frame	W10 x 12#/ft., I-Beam			
Side Rails	6 x 2, 3/16 Wall Tube			
Cross Members	3" C-Channel (16" On-Center)			
Coupler	Adjustable 2-5/16" Gooseneck Coupler			
Jack	Dual Setback HD 12K Drop Leg Jacks with Toolbox (Between Uprights), Tool Tray and Winch Receiver Tube (In Neck)			
Axles	Easy Lube Hubs with Brakes		Oil Bath Hubs with Brakes	
Suspension	Slipper Leaf Spring			
Tires	235/80R16 LRE		215/75R17.5 LRJ LRJ	
Wheels	16", 8 on 6.5, Radial		17.5", 8 on 6.5, Radial	
Decking	2 x 6 Pressure Treated Pine			
Lights	All LED Lights			
Electric Plug	7-Way RV-Style Molded Plug			
Finish	Industrial Grade Polymer Finish, High Gloss Black			
Overall Length	378"	426"	378"	426"
Deck Height	34"	34"	34"	34"
Coupler Height	Adjustable 31" - 39-3/4"			
Hydraulic Hoist	Dual Ram (Power Up / Power Down)			
Pump	3000 PSI Pump with Reservoir			
Battery	Group 24 Deep Cycle			
Load Angle	15 Degrees			

Additional configurations available. Refer to the dealer portal or contact your sales representative for more information.



Specifications are subject to change without notice, please reference dealership for final specifications.