

HEAVY DUTY LOW PROFILE HYDRAULIC BEAVERTAIL DECKOVER

- Pierced I-Beam Frame
- Cross Trac Bracing
- Safety Chains
- Breakaway Switch with Battery
- EverLink™ Wiring Harness
- Sealed Brake Connections
- 10' Hydraulic Beavertail
- Diamond Plate Deck Over Wheels
- (10) 5/8" D-Rings
- Chain Spools
- Stake Pockets and Rub Rail
- Spare Tire Carrier
- Side Steps
- Underbody Side Mount Control Box
- Tool Tray and Winch Receiver Tube (In Neck)
- Battery Charger, 110-Volt
- HD 5" Bore Twin Lift Cylinder in Beavertail
- Limited 3-Year Warranty



	8.5 x 20+10, 22.5K	8.5 x 20+10, 25.9K	8.5 x 20+10, 30K
Model #	ST-HBD10230-225G	ST-HBD10230-259G	ST-HBD10230-300G
GVWR (lbs)	22500	25900	30000
GAWR (lbs/axle)	10000	12000	15000
Curb Weight	6520	6680	7580
Payload	15980	19220	22420
Main Frame	W12 x 19#/ft., I-Beam		W12 x 19#/ft. I-Beam
Side Rails	6" C-Channel		
Cross Members	3" C-Channel (16" On-Center)		3" Channel (12" On-Center)
Beaver Tail	Wood Deck		
Gooseneck Coupler	Adjustable 2-5/16" Ball Coupler		
Jack	Dual Setback HD 12K Drop Leg Jacks with Toolbox (Between Uprights), Tool Tray and Winch Receiver Tube (In Neck)		
Axles	Oil Bath Hubs with Brakes		
Suspension	Slipper Leaf Spring		
Tires	235/80R16 LRE		215/75R17.5 LRJ
Wheels	16", 8 on 6.5, Radial		17.5", 8 on 275mm, Radial
Decking	2 x 6 Pressure Treated Pine		
Lights	All LED Lights		
Electric Plug	7-Way RV-Style Molded Plug		
Finish	Industrial Grade Polymer Finish, High Gloss Black		
Overall Length	497"		
Deck Height	32"		
Coupler Height	Adjustable 31" - 39.75"		
Beavertail Payload	5000 lbs		
Beavertail Lifting Capacity	8000 lbs (Center of Tail)		
Load Angle	15 Degrees		
Battery	Group 24 Deep Cycle		

Additional configurations available. Refer to the dealer portal or contact your sales representative for more information.



Specifications are subject to change without notice, please reference dealership for final specifications.