

HD LOW PROFILE SCISSOR HOIST

HYDRAULIC DUMP

- 24" Tall Sides
- Integrated Side Body Stiffening System
- Board Holders
- Safety Chains
- Breakaway Switch with Battery
- EverLink™ Wiring Harness
- Sealed Brake Connections
- Stabilizer Jack Receivers (Jacks Optional)
- 10-Gauge Floor
- (5) 1/2" D-Rings
- Stake Pockets
- Spare Tire Carrier
- Side Steps
- Integrated Tarp Mount
- Mesh Tarp Kit with Anti-Sail Kit
- Tongue Mounted HD Control Box with Key Lock
- Underbody Secure Tool Storage
- Battery Charger, 110-Volt
- Limited 3-Year Warranty



	82" x 12, 12K	82" x 12, 14K	82" x 14, 14K	82" x 16, 14K	82" x 14, 16K	82" x 16, 16K
Model #	ST-HSDU8212-120	ST-HSDU8212-140	ST-HSDU8214-140	ST-HSDU8216-140	ST-HSDU8214-160	ST-HSDU8216-160
GVWR (lbs)	12000	14000	14000	14000	16000	16000
GAWR (lbs/axle)	6000	7000	7000	7000	8000	8000
Curb Weight	3735	3955	4155	4495	4395	4735
Payload	8265	10045	9845	9505	11605	11265
Frame	5 x 2, 3/16"Tube	6 x 2, 3/16" Tube	6 x 2, 3/16" Tube	6 x 2, 1/4" Tube		
Cross Members	4" C-Channel					
Tongue	5 x 2 Tube	6 x 2 Tube	6 x 2 Tube	6 x 2 Tube	8 x 2 Tube	8 x 2 Tube
Sides	24" Tall Rigid Panels with 2" x 2" Tube Top Rail					
Coupler	Adjustable 2-5/16" Ball Coupler				Adjustable 4-Bolt Pintle Eye	
Jack	Setback 7K Drop Leg Jack	Setback HD 12K Drop Leg Jack				
Fenders	Heavy Duty Tread Plate, Double Brake					
Axles	Easy Lube Hubs with Brakes				Oil Bath Hubs with Brakes	
Suspension	Slipper Spring					
Tires	235/80R16 LRE				215/75R17.5 LRJ	
Wheels	16", 8 on 6.5, Radial				17.5", 8 on 6.5, Radial	
Decking	10 Ga. Smooth Steel					
Lights	All LED Lights					
Electric Plug	7-Way RV-Style Molded Plug					
Finish	Industrial Grade Polymer Finish, High Gloss Black					
Overall Length	198"	198	222"	246"	222"	246"
Bed Length Inside	144"	144	168"	192"	168"	192"
Bed Width Inside	82"	82	82"	82"	82"	82"
Bed Height Inside	24	24	24"	24"	24"	24"
Deck Height	29"	29	29"	29"	29"	29"
Coupler Height	Adjustable 19-27"					
Gate	Combination Barn Door Spreader Gate with Cambar					
Hydraulic Hoist	Power Up, Gravity Down					
Pump	2500 PSI	2800 PSI	2800 PSI	2500 PSI	2800 PSI	2800 PSI
Battery	Group 24 Deep Cycle			Group 31 Deep Cycle		



Specifications are subject to change without notice, please reference dealership for final specifications.