

PRO SERIES SUPER DUTY

HYDRAULIC DUMP

Nested Dump Bed
 3" x 2" Tube Top Rail
 48" Tall Rigid Panels
 Board Holders
 Safety Chains
 Breakaway Switch with Battery
 EverLink™ Wiring Harness
 Sealed Brake Connections
 Rear Stabilizer Jacks
 48" Axle Spread
 (5) 1/2" D-Rings
 Stake Pockets - Integrated into Ribbed Panel
 Spare Tire Carrier
 Side Steps
 Protected Tarp Mount
 Mesh Tarp Kit with Anti-Sail Kit
 Large Hydraulic Pump Box with Divider and Interior Light
 Battery Charger, 110-Volt
 Limited 3-Year Warranty



	82" x 16', 22.5K	82" x 18', 22.5K	82" x 20', 22.5K	82" x 16', 25.9K	82" x 18', 25.9K	82" x 20', 25.9K
Model #	ST-BSD8216-225	ST-BSD8218-225	ST-BSD8220-225	ST-BSD8216-259	ST-BSD8218-259	ST-BSD8220-259
GVWR (lbs)	22500	22500	22500	25900	25900	25900
GAWR (lbs/axle)	10000	10000	10000	12000	12000	12000
Curb Weight	7480	7800	8120	7900	8260	8610
Payload	15020	14700	14380	18000	17640	17290
Frame	W10x19 Beam					
Cross Members	3" Structural C-Channel					
Tongue	W10x19 Beam					
Sides	48" Tall Rigid Panels with 3" x 2" Tube Top Rail					
Coupler	Adjustable 4-Bolt Pintle Eye					
Jack	Set Back HD 2-Speed 12K Dropleg					
Fenders	Heavy Duty Treadplate, Double Break					
Axles	Oil Bath Hubs with Brakes			Oil Bath Hubs with Brakes		
Suspension	Slipper Spring					
Tires	235/75R17.5 LRJ			235/75R17.5 LRJ		
Wheels	17.5", 8 on 6.5, Radial					
Decking	7 gauge, Smooth Steel					
Lights	ALL LED Lights					
Electric Plug	7 Pole RV Molded Flat Blade					
Finish	Industrial Grade Polymer Finish, High Gloss Black					
Overall Length	265"	289"	313"	265"	289"	313"
Bed Length Inside	193"	217"	241"	193"	217"	241"
Bed Width Inside	82"					
Bed Height Inside	48"					
Deck Height	28.75"			29.5"		
Coupler Height	Adjustable 21-30"					
Gate	Combination Barn Door Spreader Gate with Cambar					
Hydraulic Hoist	Power Up, Gravity Down					
Pump	3000 PSI					
Battery	Group 31 Deep Cycle					



Specifications are subject to change without notice, please reference dealership for final specifications.