## STANDARD DUTY FLATBED

## **DECKOVER**

HD Tube Bulkhead Safety Chains Breakaway Switch with Battery EverLink™ Wiring Harness Sealed Brake Connections (6) 1/2" D-Rings Stake Pockets and Rub Rail Adjustable Spare Tire Carrier Limited 3-Year Warranty



		8.5 x 18	8.5 x 20	8.5 x 22
Model #	Bumper Pull	ST-SD0F10218-150	ST-SD0F10220-150	ST-SD0F10222-150
	Gooseneck	ST-SD0F10218-150G	ST-SD0F10220-150G	ST-SD0F10222-150G
SKU #	<b>Bumper Pull</b>	6S2T35	6S4T55	6S7T05
	Gooseneck	7S2T35	7S4T55	7S7T05
GVWR (lbs)		15000	15000	15000
GAWR (lbs/axle)		7000	7000	7000
Curb Weight	Bumper Pull	2685	3070	3457
	Gooseneck	3490	3870	4257
Payload	<b>Bumper Pull</b>	12315	11930	11543
	Gooseneck	11510	11130	10743
Main Frame		W10 x 12#/ft., I-Beam		
Side Rails		5" C-Channel		
Cross Members		3" C-Channel (16" On-Center)		
Coupler	<b>Bumper Pull</b>	Adjustable 2-5/16" Ball Coupler		
	Gooseneck	Adjustable 2-5/16" Gooseneck Coupler		
Jack	Bumper Pull	Setback HD 12K Drop Leg Jack		
	Gooseneck	Dual Setback HD 12K Drop Leg Jacks with Toolbox (Between Uprights), Tool Tray and Winch Receiver Tube (In Neck)		
Axles		Easy Lube Hubs with Brakes		
Suspension		Slipper Spring		
Tires		235/80R16 LRE		
Wheels		16", 8 on 6.5, Radial		
Decking		2 x 6 Pressure Treated Pine		
Lights		All LED Lights		
Electric Plug		7-Way RV-Style Molded Plug		
Finish		Industrial Grade Polymer Finish, High Gloss Black		
Overall Length	Bumper Pull	275"	299"	323"
	Gooseneck	323"	347"	371"
Deck Height		36"	36"	36"
Coupler Height	<b>Bumper Pull</b>	Adjustable 21"-29"		
	Gooseneck	Adjustable 31" - 39-3/4"		
Ramps		8' Fabricated Slide-In Ramps		

