



SPECIFICATIONS -HD LOW PROFILE POWER TILT DECK OVER TRAILER
HD DECKOVER POWER TILT 15K

	8.5 x 27	8.5 x 29	8.5 x 31	8.5 x 33
Model #	ST-DOT10222-150	ST-DOT10224-150	ST-DOT102224-150	ST-DOT102244-150
CAPACITIES				
GVWR (lbs)	15000			
GAWR (lbs/axle)	7000			
Curb Weight	4485	4930	5170	5615
Payload	10515	10070	9830	9385
CHASSIS				
Frame	10", 12 lb/ft I-Beam, Side Rails - 6" x 2" x 3/16" Steel Tube			
Tongue	10" Flange, 12 lb/ft I-Beam			
Crossmembers	3" Steel Channel			
Integrated Step(s)	Side Steps			
Coupler	Adjustable Pintle Ring			
Coupler Height	21-29			
Deck Height	34			
Tongue Jack	12K Drop Leg, Set-Back			
Bulkhead	HD Tube			
Axle	(2) 7000 lb. Slipper Spring Brake			
Hubs	Easy Lube			
Tires	ST235/80R16E 10-PR			
Wheels	16", 8-Hole Steel			
Exterior Finish	Industrial Grade Polymer Finish			
Decking	2" Pressure Treated Pine, Steel Tread Plate Over Wheels			
Tie Downs	(6) 5/8" D-Rings, Stake Pockets, Chain Spools, and Rub Rail	(8) 5/8" D-Rings, Stake Pockets, Chain Spools, and Rub Rail	(6) 5/8" D-Rings, Stake Pockets, Chain Spools, and Rub Rail	
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box			
Exterior Lights	Full LED, DOT Compliant			
Hydraulic Components	12 Volt Hydraulic Pump, Power-Up, Power-Down (Dual Ram)			
Width Tilting Deck	102			
Load Angle	15			
DIMENSIONS				
Overall Length	330	354	378	402
Deck Height	34			
Coupler Height	21-29			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -HD LOW PROFILE POWER TILT DECK OVER
TRAILER
HD DECKOVER POWER TILT GN 15K

	8.5 x 31	8.5 x 33	8.5 x 35
Model #	ST-DOT10222-150G	ST-DOT10224-150G	ST-DOT102224-150G
CAPACITIES			
GVWR (lbs)	15000		
GAWR (lbs/axle)	7000		
Curb Weight	4775	4930	5460
Payload	10225	10070	9540
CHASSIS			
Frame	10", 12 lb/ft I-Beam, Side Rails - 6" x 2" x 3/16" Steel Tube		
Crossmembers	3" Steel Channel		
Integrated Step(s)	Side Steps		
Coupler	2-5/16" Adjustable Gooseneck		
Coupler Height	31-39.75		
Deck Height	34		
Tongue Jack	Dual 12K Drop Leg		
Bulkhead	HD Tube		
Axle	(2) 7000 lb. Slipper Spring Brake		
Hubs	Easy Lube		
Tires	ST235/80R16E 10-PR		
Wheels	16", 8-Hole Steel		
Exterior Finish	Industrial Grade Polymer Finish		
Decking	2" Pressure Treated Pine, Steel Tread Plate Over Wheels		
Tie Downs	(6) 5/8" D-Rings, Stake Pockets, Chain Spools, and Rub Rail	(8) 5/8" D-Rings, Stake Pockets, Chain Spools, and Rub Rail	
Exterior Storage	Integrated Gooseneck Toolbox, Spare Tire Carrier, Tool Tray and Winch Receiver Tube (In Neck)		
Exterior Lights	Full LED, DOT Compliant		
Hydraulic Components	12 Volt Hydraulic Pump, Power-Up, Power-Down (Dual Ram)		
Width Tilting Deck	102		
Load Angle	15		
DIMENSIONS			
Overall Length	378	402	426
Deck Height	34		
Coupler Height	31-39.75		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -HD LOW PROFILE POWER TILT DECK OVER TRAILER

HD DECKOVER POWER TILT 17.6K

	8.5 x 27	8.5 x 29	8.5 x 31	8.5 x 33
Model #	ST-DOT10222-176	ST-DOT10224-176	ST-DOT102224-176	ST-DOT102244-176
CAPACITIES				
GVWR (lbs)	17600			
GAWR (lbs/axle)	8000			
Curb Weight	4825	5540	5370	5050
Payload	12775	12060	12230	12550
CHASSIS				
Frame	10", 12 lb/ft I-Beam, Side Rails - 6" x 2" x 3/16" Steel Tube			
Tongue	10" Flange, 12 lb/ft I-Beam			
Crossmembers	3" Steel Channel			
Integrated Step(s)	Side Steps			
Coupler	Adjustable 4-Bolt Pintle Ring			
Coupler Height	21-29			
Deck Height	34			
Tongue Jack	12K Drop Leg, Set-Back			
Bulkhead	HD Tube			
Axle	(2) 8000 lb. Slipper Spring Brake			
Hubs	Oil Bath			
Tires	215/75R17.5J 18-PR			
Wheels	17.5", 8-Hole Steel			
Exterior Finish	Industrial Grade Polymer Finish			
Decking	2" Pressure Treated Pine, Steel Tread Plate Over Wheels			
Tie Downs	(6) 5/8" D-Rings, Stake Pockets, Chain Spools, and Rub Rail	(8) 5/8" D-Rings, Stake Pockets, Chain Spools, and Rub Rail	(6) 5/8" D-Rings, Stake Pockets, Chain Spools, and Rub Rail	
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box			
Exterior Lights	Full LED, DOT Compliant			
Hydraulic Components	12 Volt Hydraulic Pump, Power-Up, Power-Down (Dual Ram)			
Width Tilting Deck	102			
Load Angle	15			
DIMENSIONS				
Overall Length	330	354	378	402
Deck Height	34			
Coupler Height	21-29			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -HD LOW PROFILE POWER TILT DECK OVER TRAILER

HD DECKOVER POWER TILT GN 17.6K

	8.5 x 31	8.5 x 33	8.5 x 35	8.5 x 37
Model #	ST-DOT10222-176G	ST-DOT10224-176G	ST-DOT102224-176G	ST-DOT102244-176G
CAPACITIES				
GVWR (lbs)	17600			
GAWR (lbs/axle)	8000			
Curb Weight	5115	5540	5660	5320
Payload	12485	12060	11940	12280
CHASSIS				
Frame	10", 12 lb/ft I-Beam, Side Rails - 6" x 2" x 3/16" Steel Tube			
Crossmembers	3" Steel Channel			
Integrated Step(s)	Side Steps			
Coupler	2-5/16" Adjustable Gooseneck			
Coupler Height	31-39.75			
Deck Height	34			
Tongue Jack	Dual 12K Drop Leg			
Bulkhead	HD Tube			
Axle	(2) 8000 lb. Slipper Spring Brake			
Hubs	Oil Bath			
Tires	215/75R17.5J 18-PR			
Wheels	17.5", 8-Hole Steel			
Exterior Finish	Industrial Grade Polymer Finish			
Decking	2" Pressure Treated Pine, Steel Tread Plate Over Wheels			
Tie Downs	(6) 5/8" D-Rings, Stake Pockets, Chain Spools, and Rub Rail	(8) 5/8" D-Rings, Stake Pockets, Chain Spools, and Rub Rail		
Exterior Storage	Integrated Gooseneck Toolbox, Spare Tire Carrier, Tool Tray and Winch Receiver Tube (In Neck)			
Exterior Lights	Full LED, DOT Compliant			
Hydraulic Components	12 Volt Hydraulic Pump, Power-Up, Power-Down (Dual Ram)			
Width Tilting Deck	102			
Load Angle	15			
DIMENSIONS				
Overall Length	378	402	426	450
Deck Height	34			
Coupler Height	31-39.75			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.